Varn International, Inc., a Flint Group Company

14909 N. Beck Road Plymouth, MI 48180

For Product Questions call: (800) 336-VARN(8276) For Health and Safety Questions call: (800) 336-VARN(8276)

After Hours Emergency Health/Safety Questions: (800) 391-0698 Prosar (US/Canada) 24 Hour Emergency Spill Contact call: (800) 424-9300 Chemtrec (US/Canada)

Material Safety Data Sheet

I. PRODUCT AND COMPANY IDENTIFICATION

Product Name: WASH V-60 PLUS **Product Code:** 650-B010063 MSDS Code: MSD-00939965

Revision Number:

2011-02-26 11:25:05 **Revision Date:**

II. COMPOSITION/INFORMATION ON INGREDIENTS

CAS# **Chemical Name** % 64742-48-9 Naphtha (petroleum), hydrotreated heavy ~ 100

Please see Section VIII for product and component exposure guidelines.

Components not listed are not physical or health hazards as defined in 29 CFR 1910.1200 (Hazard

Communication Standard).

III. HAZARDS IDENTIFICATION

HMIS Rating Health: 1 Flammability: 2 Reactivity: 0

This product falls under the following WHMIS class:

B3

Ingestion, Inhalation, Skin contact, Eye contact Routes of Entry:

Target Organs: Lungs

Immediate (Acute) Health Effects by Route of Exposure

Inhalation: Can cause minor respiratory irritation, dizziness, weakness, fatique, nausea, and

headache.

Skin Contact: Can cause minor skin irritation, defatting, and dermatitis. **Eve Contact:** Can cause minor irritation, tearing and reddening.

Irritating to mouth, throat, and stomach. Can cause abdominal discomfort. Ingestion:

nausea, vomiting and diarrhea. Harmful if swallowed. May cause systemic

poisoning.

Long-Term (Chronic) Health Effects

Reproductive and No data available to indicate product or any components present at greater than

0.1% may cause birth defects. **Developmental:**

Mutagenicity: No data available to indicate product or any components present at greater than

0.1% is mutagenic or genotoxic.

Inhalation: Upon prolonged and/or repeated exposure, can cause minor respiratory

irritation, dizziness, weakness, fatigue, nausea, and headache.

WASH V-60 PLUS

Skin Contact: Upon prolonged or repeated contact, can cause minor skin irritation, defatting,

and dermatitis.

Ingredients of this product appear on the following OSHA identified carcinogen lists at >= 0.1% by

weight (yes/no):

OSHA No NTP No IARC 1 & 2A No NIOSH No

IARC 2B No

IV. FIRST-AID MEASURES

Inhalation: Remove to fresh air. If breathing is difficult, have a trained individual administer

oxygen. If not breathing, give artificial respiration and have a trained individual

administer oxygen. Get medical attention immediately.

Eyes: Use an eye wash to remove a chemical from your eye regardless of the level of

hazard. Flush the affected eye for at least twenty minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Seek medical advice after

flushing. Seek medical advice if symptoms persist

Skin Contact: Wash with soap and water. Get medical attention if irritation develops or persists.

Wash clothing before reuse.

Ingestion: Do not induce vomiting and seek medical attention immediately. Drink two

glasses of water or milk to dilute. Provide medical care provider with this MSDS.

V. FIRE FIGHTING MEASURES

Flammability Combustible NFPA IIIA (NFPA description only; not to be used for shipping

Summary: purposes)

Extinguishing Media: Use alcohol resistant foam, carbon dioxide, dry chemical, or water spray when

fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the fire. Do not direct a

water stream directly into the hot burning liquid.

Fire and/or Explosion

Hazards:

Material may be ignited if preheated to temperatures above the flash point in the

presence of a source of ignition. Combustible Liquid. Can form explosive

mixtures at temperatures at or above the flash point.

Fire Fighting
Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe

Protection: distance and a protected location due to the potential of hazardous vapors and

decomposition products.

Hazardous

Combustion Products:

Carbon dioxide, Carbon monoxide

Flash Point: >60 C (140 F) - < 93 C (200 F) Firepoint: Firepoint not determined.

Autoignition Temperature: 253 deg C 487 deg F

Upper Flammable/Explosive Limit, % in air: 5.0 Lower Flammable/Explosive Limit, % in air: 0.8

VI. ACCIDENTAL RELEASE MEASURES

Personal PrecautionsNo health affects expected from the clean-up of this material if contact can be avoided. Follow personal protective equipment recommendations found in

Section VIII of this MSDS

VII. HANDLING AND STORAGE

Product Use: Press Wash

WASH V-60 PLUS

Page 2 of 4

Mildly irritating material. Avoid unnecessary exposure. As with all chemicals, **Handling** Precautions: good industrial hygiene practices should be followed when handling this material.

Store in a cool dry place. Isolate from incompatible materials. **Storage Conditions:**

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

General room ventilation might be required to maintain operator comfort under **Engineering**

normal conditions of use. Measures:

Respiratory General or local exhaust ventilation is the preferred means of control. If general

or local exaust ventilation is not available or sufficient to control or eliminate Protection: symptoms as described in Section III, respiratory protection should be used.

Wear safety glasses with side shields when handling this product. Wear additional eve protection such as chemical splash goggles and/or face shield

when the possibility exists for eye contact with splashing or spraying liquid, or

airborne material. Have an eye wash station available.

Not normally considered a skin hazard. Where use can result in skin contact, Skin Protection:

> practice good personal hygiene and wear a barrier cream and/or impervious surgical style gloves. Wash hands and other exposed areas with mild soap and

water before eating, drinking, and when leaving work.

Gloves: Wear impervious material. Butyl rubber or Nitrile

Exposure Guidelines:

Eve Protection:

CAS# **Chemical Name OSHA Exposure Limits** ACGIH TLV -ACGIH **IDLH** TWA STEL 64742-48-9 Naphtha (petroleum). No TLV No STEL Not on list hydrotreated heavy

If this product is provided in a dry powder state it should be considered a nuisance dust (PEL 10 mg/m3).

If the processing of this product produces a mist it should be considered to be an oil mist with a PEL of 5 mg/m3.

IX. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid Color: Clear

Odor: Petroleum or solvent Solubility in Water: Not determined

Vapor Pressure (mmHg @ 20 deg. C): 0.5 98.71 **Volatile Organic Chemicals % by wt:** VOC lb/gal 6.5

Boiling Point: 160 deg C 320 deg F

Specific Gravity: 0.79 **Bulk Density (lbs/Gal):** 6.58 **Bulk Density (kg/L):** 0.79

X. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to Avoid: Temperatures above flash point in combination with sparks, open flames, or

other sources of ignition.

Materials to

Strong oxidizing agents.

Avoid/Chemical Incompatibility:

WASH V-60 PLUS

XI. TOXICOLOGICAL INFORMATION

Component Toxicology Data (NIOSH):

CAS# Chemical Name LD50/LC50

64742-48-9 Naphtha (petroleum), hydrotreated Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rabbit >3160 mg/kg

neavy

XII. DISPOSAL CONSIDERATIONS

Waste Description

Spent or discarded material is not expected to be a hazardous waste.

for Spent Product:

Disposal Methods: Dispose in accordance with Federal, State, Provincial and Local regulations.

Material may be compatible with industrial waste incineration or inclusion in a fuel blending program. This characterization is subject to approval by your waste

management contractor. This material should be recycled if possible.

XIII. REGULATORY INFORMATION

TSCA Status All ingredients of this product are listed or are excluded from listing on the U.S.

Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

Chemical Name	CAS#	Regulation	Percentage
Not on list		CERCLA	
Hydrotreated heavy naphtha	64742-48-9	NPRI (Cdn)	98.7
Not on list		PROP 65	
Not on list		SARA 313	
Not on list		SARA EHS	

The following items require export notification for TSCA

Chemical Name TSCA 12b list section

Not on list

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations and the MSDS contains information required by the Controlled Products Regulations.

XIV. TRANSPORTATION INFORMATION

49CFR/TDG - Non-bulk: GROUND SHIPMENTS NOT REGULATED IN PACKAGINGS OF 119 GAL

(450 L) OR LESS.

49CFR/TDG - Bulk: NA1993, COMBUSTIBLE LIQUID, N.O.S. (NAPHTHA), PGIII, ERG128

IATA - Non-bulk: NOT REGULATED NOT REGULATED NOT REGULATED

XV. ADDITIONAL INFORMATION

References:

Disclaimer: Varn International, Inc. a Flint Group Company has prepared this Material Safety Data Sheet ("MSDS") in compliance with 29 CFR 1910.1200, understands that its customers may use this MSDS to comply with that section, and believes that the data set forth herein are accurate as of the date hereof; however, this MSDS shall not constitute a warranty with respect thereto.