

hydrocarbons

ALLIED PRESSROOM CHEMISTRY

MATERIAL SAFETY DATA SHEET

	5	SECTIO	N 1 PR	ODUCT IE	DENTIFIC <i>A</i>	NOITA	AND USE		
PRODUCT IDENTIFIER : ALLIED DYNAKLEAN (Roller Cleaner for lithographic presses							0-minimal, 1-slight, 2- HEALTH HA	moderate, 3-serious, 4-severe ZARD: 1	
MANUFACTURER'S NAME: ALLIED PRESSROOM CHEMISTRY.							FIRE HAZAR REACTIVITY PROTECTIV		
STREET ADDRESS 2040 LEE STREET, HOLLYWOOD, FLORIDA, 33020, USA							M A		
OFFICE TELEPHONE: 800-327-8487		FAX: 954-923-	6462		24 HR. EMERGENCY TELEPHO 800-424-9300 CHEMTREC		Safety Glasses G	Protective loves Apron	
THIS IS AN INDUSTRIAL PRODUCTS POSE AN IN COMPLETE LABEL AND	IHEREI	NT HEAL	TH RISK. E	BEFORE USE	ALWAYS RI		DO NOT BREATHE VA	APORS. DO NOT GET IN EYES, N CLOTHING. DO NOT INGEST	
SECTION 2 – INGREDIENT INFORMA							ATION		
**These ingredients are subject to the reporting			CAS NUMBER		HAZARD DATA				
requirements of SARA 313 and 40 CFI Aromatic petroleum distilla This ingredient contains app Xylene* 2-5% cas#1330-20 13-7 No exposure levels este Ethylbenzene* 0-0.3% cas	ates proximat -7 OSHA ablished	ely: A PEL-100 ; Diethylb	enzene 1-5	nene* 1-4% co % cas#25340-		HA PEL :		nzenes* 30-50% cas#25551-	
	ΛΙΙ INI	PEDIENT	TO ADELICT	ED IN THE HE	TOVIC SUIDST	TANCE C	CONTROL ACT (TSCA)		
	ALL IN	3KEDIEN I			HYSICAL				
PHYSICAL STATE THICK LIQUID	ODOR AND APPEARANC Viscous white, emulsion, hydrocarbon odor			WATER SOL Miscible		PH Not applicable		SPECIFIC GRAVITY 0.80	
VAPOR PRESSURE (MM Hg) or VOC materials <3.0 @ 20°C	VAPO (AIR=1 >1	R DENSIT I)	Υ	EVAPORATION RATE (Butyl acetate = 1) <1		BOILING POINT (°F) 212 F initial		V.O.C.'s 10% by Mass 0.8 lb per Gallon (96 g/l)	
		SEC	CTION 4	- FIRE AN	ND EXPLO	SION	DATA		
FLAMMABILITY YES □ NO ■ IF YES, UNDER WHICH CONDITIONS? ▶ Material may burn under fire							e conditions		
EXTINGUISHING MEDIA CARBON DIOXIDE, DRY CHEMICAL, UNIVERS							IGHTING PROCEDURES: d breathing apparatus.		
FLASHPOINT (°F) AND METHOD > 200 F by TCC					MABLE LIMIT E) : Unknown		LOWER FLAMMABLE LIMIT (% BY VOLUME): Unknown		
AUTOIGNITION TEMPER Not known		HAZARDOUS COMBUSTION PRODUCTS Oxides of carbon and hydrocarbons.							
EXPLOSION DATA NOT KNOWN			SENSITIVITY TO SENSIT				STATIC DISCHARGE		
_					EACTIVITY			_	
CHEMICAL STABILITY YES ■ NO □ CONDITION None				ONS CONTRIBUTING TO HAZARDOUS POLYMERISATION					
INCOMPATIBILTY WITH Strong oxidizing agents, s				ng bases					
HAZARDOUS DECOMPOSITION PRODUCTS: In contact with open flame or incandescent material will liberate carbon dioxide, carbon monoxide and									



PRODUCT IDENTIFIER • ALLIED DYNAKLEAN

ROUTES OF ENTRY

SKIN CONTACT ■

SKIN ABSORPTION ■

EYE CONTACT ■

INHALATION ■

INGESTION ■

ACUTE EXPOSURE TO PRODUCT: Inhalation - Inhalation can cause severe irritation of the respiratory tract, signs of central nervous system depression, dizziness nausea and headache. Eye - Will cause severe irritation, burning, redness and tearing. Skin - Can cause irritation, redness burning and drying. Ingestion causes irritation of the digestive tract. Aspiration into the lungs can lead to pulmonary odema and chemical pneumonia which can prove fatal. Prolonged over-exposure can lead to narcosis, respiratory failure, coma.

CHRONIC EXPOSURE TO PRODUCT: Prolonged skin contact may aggravate an existing dermatitis. Prolonged and repeated exposure to the pure solvent contained in this product has been reported to cause permanent brain and central nervous system damage.

CARCINOGENICITY: Ethylbenzene cas#100-41-4 present at less than 0.03% is listed as IARC Group 2B - a possible human carcinogen.

TARGET ORGAN EFFECTS: Over-exposure has been linked to blood, liver and kidney abnormalities in animal studies. Has been linked to birth defects in animal studies, may harm fetus at exposure levels harmful to mother.

EMERGENCY FIRST AID PROCEDURES:

EYES: Flush with running water for at least 15 minutes. Seek medical attention.

SKIN: wash affected area with soap and water. Remove contaminated clothing and launder before re-use.

INHALATION: Remove victim to fresh air. Administer oxygen and/or artificial respiration if breathing difficulties occur. Seek medical

INGESTION: Do not induce vomiting. Material is an aspiration hazard, may enter lungs and cause lung damage. Seek immediate medical attention.

SECTION 7 - PREVENTATIVE MEASURES

GLOVES
Nitrile for incidental, non-immersion contact.

RESPIRATOR: Use NIOSH approved SCBA in emergency situations or confined areas.

EYE (SPECIFY)

Splash proof goggles or face shield

CLOTHING: Boots, aprons, or chemical suits should be used when necessary to prevent skin contact.

ENGINEERING CONTROLS (SPECIFY, EG. VENTILATION, ENCLOSED PROCESS): Use local exhaust or dilution ventilation as appropriate to control exposure below permissible levels. Vapors are heavier than air and will collect in low areas

LEAK AND SPILL PROCEDURE: Extinguish all sources of ignition. Provide maximum ventilation. Dike area to contain spill. Take precautions to prevent contamination of ground and surface waters. Recover spilled material using absorbent material such as vermiculite and sweep into closed containers for disposal.

WASTE DISPOSAL: Contaminated vermiculite or porous surface must be disposed of in a permitted hazardous waste facility. Recovered liquids may be reprocessed or incinerated in a permitted hazardous waste facility. In all cases material should be disposed of in accordance with all applicable regulations.

HANDLING PROCEDURES AND EQUIPMENT: Keep container closed when not in use. Store only in closed, properly labeled containers. Store as COMBUSTIBLE LIQUID. Store in a cool, dry, well ventilated area away from heat sparks and open flames. Treat empty containers as containing hazardous residues.

ADDITIONAL INFORMATION

.CALIFORNIA PROPOSITION 65: This regulation does not address "de minimis" levels. Therefore even trace amounts of chemicals on these lists must be identified. Trace quantities refer low levels of materials whose exact concentrations may not always be determined because of their minuteness.

This product contains the following chemicals known by the state of California to cause cancer: benzene, dioxane, acetaldehyde, formaldehyde, ethylene oxide. This product contains following chemicals known by the state of California to cause reproductive harm: benzene, toluene, ethylene oxide.

SHIPPING INFORMATION: Not regulated for shipping purposes

SECTION 9 - PREPARATION AND DATE OF MSDS

PREPARED BY (GROUP DEPARTMENT, ETC.)
ALLIED PRESSROOM CHEMISTRY TECHNICAL SERVICES DEPARTMENT

PHONE NUMBER 1-800-327-8487 DATE May 2005

The above information is believed to be correct as of the date hereof and is based on data supplied by raw material suppliers, however, no warranty of merchantability, fitness for use, or any other warranty is expressed or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with each use. Since the information contained herein may be applied under conditions beyond our control and with which we are unfamiliar, and since the data made available subsequent to the date hereof may suggest modifications of the information, we do not assume responsibility for the results of its' use. This information is furnished on the condition that the person receiving it shall make his own determination as to the suitability of the material for his particular purpose and on the condition that he assume risk of his use thereof.