

MATERIAL SAFETY DATA SHEET

The Anchor MSDS information provided on this site is updated on a monthly basis and complies with OSHA's Hazard Communication Standard (CFR 1910.1200) and the American National Standards Institute (ANSI) Standard for Material Safety Data Sheets (ANSI Z400.1).

Finished Goods Catalog

8590 - MASTERLITH(R) DON'S PLATE CLEANER/SCRATCH REMOVER

Manufacturer Name

ANCHOR LITHKEMKO, A SUBSIDIARY OF FUJI HUNT

SECTION 1 - COMPANY IDENTIFICATION

Catalog / Sub-assembly Number: 8590 ANCHOR LITHKEMKO, A SUBSIDIARY OF FUJI HUNT 50 Industrial Loop North Orange Park, FL 32073

TRANSPORTATION EMERG	ENCIES (24HR)
Inside US/Canada	800-424-9300
Outside US/Canada	703-527-3887
(accepts collect	calls)
MEDICAL EMERGENCIES	(24HR)
Prosar	877-935-7387
NON-EMERGENCY	
EHS Info	904-264-3500
General Info	800-354-2300

FOR INDUSTRIAL USE ONLY.....USE ONLY AS DIRECTED.....DO NOT TAKE INTERNALLY!

SECTION 2 - COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients	CAS Number	Wt.%	OSHA PEL	ACGIH
			(mg/m3)	(mg/m3)
Butyl Cellosolve	111-76-2	5-10%	240 skin	96.6 skin
Sodium Metasilicate	6834-92-0	0.5-1.5%	15ppm	10ppm
Sodium Tripolyphosphate	7758-29-4	0.5-1.5%	NE	NE
Aryl Sulfonate	TSRN 06-0836	0.5-1.5%	NE	NE
	-331-5032			
Water	7732-18-5	80-100%	NE	NE

NE=Not Established STEL=Short Term Exposure Limit C=Ceiling Limits

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Avoid contact with eyes, skin or clothing. Avoid breathing mist or vapor. Do not swallow. Wear chemical safety goggles & neoprene gloves and apron. Wash

thoroughly after handling. Keep container closed when not in use. Use only with adequate ventilation. May produce hazardous gases under fire conditions. During emergencies, wear equipment to protect eyes, skin and respiratory tract. Dike or absorb spills to keep material and run-off from entering sewer or waterways. Use water spray to cool containers and disperse vapors. Box may contain multiple containers having multiple components. Consult all MSDSs.

HMIS: Health: 2 Flammability: 1 Reactivity: 0 Protection: B NFPA: Health: 2 Flammability: 1 Reactivity: 0 Spec. Haz.: None Hazard Rating: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe A = Gloves B = Gloves & Goggles C = Gloves, Goggles & Apron D = Face Shield, Gloves, Goggles & Apron UN NO: None DOT GUIDE: ERG Guide 111

Potential Health Effects:

Skin:

Contact causes irritation. Eves: Causes irritation.

Inhalation: Irritant to respiratory tract and mucous membranes.

Ingestion: Ingestion of product may cause nausea and vomiting.

Conditions aggravated by exposure:

None expected except those associated with acute effects.

SECTION 4 - FIRST AID MEASURES

Eye Contact: Immediately flush with COOL water for 15 minutes. Call a physician. Skin Contact: In case of skin contact; wash with soap and water for 15 minutes. Call a physician. In case of ingestion; induce vomiting upon medical advice. Call a physician. Ingestion: Inhalation: Immediately remove victim to fresh air. Call a physician for further

SECTION 5 - FIRE FIGHTING MEASURES

Flammable Properties			
Flash Point:	>200	Deg F	TCC
Autoignition Temperature:	N/A	deg F	(CC)
Explosion Limits: Lower:	N/A	vol.%:	Not Tested
Upper:	N/A	vol.%:	

Extinguishing Media:

recommendations.

Choose extinguishing media suitable for the surrounding materials, such as water spray, dry chemical, alcohol foam or carbon dioxide. Unsuitable Extinguishing Media:

No restrictions on media based on knowledge of this material. Fire Fighting Instructions:

Water spray should be used to cool fire exposed containers and to disperse un-ignited vapors. Use NIOSH/MSHA approved positive pressure self-contained breathing apparatus when material has ignited or becomes involved in a fire. Try to remove material containers from fire area if can be accomplished without risk to personnel.

Evacuate area and fight fire from a safe distance. Call your local fire department. Wear positive pressure, breathing apparatus and protect eyes and skin. Use water to cool fire-exposed containers, to protect personnel and to disperse vapors and spills. Fire media run-off can damage the environment. Dike and collect media used to fight fire.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Small Spills:

For small incidental spills and leaks wear chemical safety goggles, and neoprene gloves and apron or coveralls. Isolate area of spill by diking. Stop source of leak. Add dry absorbent. Clean up and place in an approved D.O.T. container and seal. Wash all contaminated clothing before reuse, and discard contaminated leather shoes.

Large Spills:

For larger spills requiring emergency response, neoprene boots and respiratory protection may also be required. Follow OSHA regulations and NIOSH recommendations for respirator use (29 CFR 1910.134 and NIOSH Pub. 87-108) and emergency response (see 29 CFR 1910.120). Isolate area of spill by diking. Stop source of leak. Add dry absorbent. Clean up and place in an approved D.O.T. container and seal. Wash all contaminated clothing before reuse, and discard contaminated leather shoes. Call the emergency telephone number shown on the front of this sheet.

SECTION 7 - HANDLING / STORAGE

Handling:

Avoid contact with eyes, skin or clothing. Avoid breathing mist or vapor. Do not swallow. Wear chemical safety goggles and neoprene gloves and apron. Wash thoroughly after handling. Keep container closed when not in use. Use only with adequate ventilation.

Storage:

Store in a cool, dry, well-ventilated area away from all sources of ignition. Keep containers closed when not in use.

SECTION 8 - EXPOSURE CONTROL AND PERSONAL PROTECTION

Ventilation:

Good general ventilation should be sufficient for most processing operations. Vent work area to ensure airborne concentrations are below the current occupational exposure limits. Ten (10) or more room air changes per hour containing a minimum of 15% fresh air will meet these requirements. Consult ASHRAE 62-1989 for further requirements.

Personal Protective Equipment

Respiratory Protection: If used under normal operating conditions and with adequate ventilation, respiratory protection is not required. However, refer to OSHA 29 CFR 1910.13 4.

Skin Protection:	Chemical	resista	ant gloves
Eye Protection:	Chemical	safety	goggles

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear, bl	ue, aque	eous	liquid
Odor: Mild citr	us odor		
Change in Physical Sta	ate:		
Boiling Point:	>100	deg	C
Melting Point:	N/D	deg	F
Specific Gravity:	0.99		Water=1
Vapour Pressure:	1.57		mmHg @ 20C
Viscosity:	N/A		
Solubility in Water:	Complet	ce	
pH Value:	12.4		
VOC (lbs/gal):	0.70	(USE	IPA Method 24)
	Non-Pho	otocł	nemically Reactive

SECTION 10 - STABILITY AND REACTIVITY

Hazardous Polymerization:

Hazardous polymerization WILL NOT occur if product is used and stored as directed. Product is stable if used and stored as directed. Hazardous Decomposition Products: Oxides of Nitrogen; Oxides of Carbon Materials and Conditions to Avoid: Keep containers and liquids away from all potential sources of ignition. Keep away from excess heat. Avoid contact with strong oxidizers, strong acids and strong bases. SECTION 11 - TOXICOLOGICAL INFORMATION Product Information LD50 (oral, rat): No Data Available Acute Overexposure: Skin, eye, mucous membrane and respiratory tract irritant. Chronic Overexposure: Prolonged or repeated skin contact may cause allergic reaction and dermatitis. Ingredient information: Chronic overexposure to Butyl Cellosolve in high concentrations has caused anemia, liver and blood abnormalities, and kidney and lung damage in laboratory animals; may cause maternal toxicity. SECTION 12 - ECOLOGICAL INFORMATION Ecotoxicity Data: No Data Available Chemical Fate Data: No Data Available SECTION 13 - DISPOSAL CONSIDERATIONS Hazardous Waste Characteristic: None Recommendation: Dispose of contaminated product, empty containers and materials used in cleaning up spills or leaks in a manner approved for this material. Consult appropriate federal, state and local regulatory agencies to ascertain proper disposal procedures. Discharge of processing effluent to the sewer may require a permit. DO NOT discharge effluent solutions to septic systems. SECTION 14 - TRANSPORTATION INFORMATION Ground Shipping Information Proper Shipping Name: Chemicals, N.O.I., Not D.O.T. regulated. Hazard Class: None UN/NA Number: None Packing Group: None Air (ICAO/IATA) Shipping Information Proper Shipping Name: Chemicals, N.O.I., Not D.O.T. regulated. None Hazard Class: UN No: None Packing Group: None Subsidiary Risk: None UN/DOT Labels Needed: None International Maritime Organization (IMO) Additional Shipping Class: IMDG Code: Not Applicable Amdt. Code: Amdt. N/A HTS Code: HTS#3814.00.5000.0 Product is labeled in accordance with US D.O.T. 49 CFR. Further information:

```
Please call (904) 264-3500 for further D.O.T. information.
```

N

SECTION 15 - REGULATORY INFORMATION

**Note: The ingredient information listed in this section is provided for reporting requirements as dictated by USEPA, state and local regulation. If ingredient is listed in this section but not in Section 2, then the concentration of this ingredient is below de minumis (less than 0.1%). U.S. FEDERAL REGULATIONS: 313 = SARA Title III Section 313 (40 CFR 372 -- Toxic Release Inventory) 355 = SARA Title III Section 302 (40 CFR 355 -- Extremely Hazardous Substance) 302 = SARA Title III Section 304 (40 CFR 302 -- Hazardous Substance List) CWA = Clean Water Act Priority Pollutants List CAA = Clean Air Act 1990 Hazardous Air Contaminants HAP = Clean Air Act - HON Rule - HAPs CAS Number 313 355 302 CWA CAA HAP Ingredients 111-76-2 Y N Y N Y 6834-92-0 N N N N N Butyl Cellosolve Y Sodium Metasilicate Ν Sodium Tripolyphosphate 7758-29-4 N N Y N N Ν TSRN 06-0836 N N N N N N Aryl Sulfonate

	-331-5032					
Water	7732-18-5	Ν	Ν	Ν	Ν	Ν

TSCA 12(b) Export Notification CAS NUMBER CHEMICAL NAME 107-21-1 ETHYLENE GLYCOL

TOXICITY INFORMATION: IRC1 = IARC Group 1 Human Carcinogens List IRC2 = IARC Group 2 Human Carcinogens List (limited human data) IRC3 = IARC Group 2B Human Carcinogens List (sufficient animal data) NTP = NTP Known Carcinogens List OSHA = OSHA Known Carcinogens List

Ingredients	CAS Number	IRC1	IRC2	IRC3	NTP	OSHA
Butyl Cellosolve	111-76-2	N	Ν	Ν	N	N
Sodium Metasilicate	6834-92-0	N	Ν	Ν	N	N
Sodium Tripolyphosphate	7758-29-4	N	Ν	N	N	N
Aryl Sulfonate	TSRN 06-0836	N	Ν	Ν	N	N
	-331-5032					
Water	7732-18-5	Ν	Ν	Ν	Ν	N

STATE REGULATIONS:

FL = Florida Hazardous Substance ListMA = Massachusetts Right-To-Know ListMI = Michigan Critical Materials ListMN = Minnesota Hazardous Substance ListNJ = New Jersey Right-To-Know ListPA = Pennsylvania Right-To-Know List

Ingredients	CAS Number	PA	NJ	MN	MI	MA	FL
Butyl Cellosolve	111-76-2	Y	Y	Y	Ν	Y	Y
Sodium Metasilicate	6834-92-0	Ν	Ν	Ν	Ν	Ν	Ν
Sodium Tripolyphosphate	7758-29-4	Y	Y	Ν	Ν	Y	Ν
Aryl Sulfonate	TSRN 06-0836	Ν	Ν	Ν	Ν	Ν	Ν
	-331-5032						
Water	7732-18-5	Ν	Ν	Ν	Ν	Ν	Ν

The following information is required by the State of California's Safe Drinking Water and Toxic Enforcement Act of 1986 or Proposition 65. This regulation does not address di minimus levels; therefore, even trace amounts of chemicals included on these lists must be noted with the "Safe Harbor" wording.

WARNING: Known to the State of California to cause cancer: ****None Listed**** WARNING: Known to the State of California to cause developmental toxicity: ****None Listed**** WARNING: Known to the State of California to cause female reproductive effects ****None listed**** WARNING: Known to the State of California to cause male reproductive effects: ****None listed****

SECTION 16 - OTHER INFORMATION

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.