

# MATERIAL SAFETY DATA SHEET

## 1. Product and Company Identification

**Product number** NW2300  
**Product name** **No Wash Up Spray**  
**Effective date** 01-Mar-2011  
**Company information** Burnishine Products  
Lake Villa, IL 60046 United States  
**Company phone** General Assistance 1-800-818-8275  
**Emergency telephone US** 800-424-9300  
**Emergency telephone outside US** 703-527-3887  
**Version #** 05  
**Supersedes date** 01-Mar-2011

## 2. Hazards Identification

**Emergency overview** Aerosol. EXTREMELY FLAMMABLE. Will be easily ignited by heat, spark or flames. CONTENTS UNDER PRESSURE. Harmful in contact with eyes. Prolonged exposure may cause chronic effects.

**Potential health effects**

**Routes of exposure** Eye contact. Skin contact. Ingestion.

**Eyes** Contact may irritate or burn eyes. Eye contact may result in corneal injury.

**Skin** Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

**Inhalation** Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Prolonged inhalation may be harmful.

**Ingestion** Exposure by ingestion of an aerosol is unlikely. May cause delayed lung damage. Components of the product may be absorbed into the body by ingestion.

**Target organs** Central nervous system. Lungs.

**Chronic effects** Conjunctiva. May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage. Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. May cause delayed lung injury.

**Signs and symptoms** Discomfort in the chest. Corneal damage. Narcosis. Coughing. Conjunctivitis. Defatting of the skin. Components of the product may affect the nervous system. Skin irritation.

## 3. Composition / Information on Ingredients

Components	CAS #	Percent
n-Butane	106-97-8	20 - 30
Synthetic Isoparaffinic Hydrocarbon	64742-47-8	15 - 20
Isopropyl Alcohol	67-63-0	10 - 15
Aliphatic Petroleum Solvent	64742-89-8	10 - 15
Propane	74-98-6	10 - 15
Butylated Hydroxytoluene	128-37-0	8 - 10
Non-hazardous and other components below reportable levels		1 - 2.5

## 4. First Aid Measures

### First aid procedures

**Eye contact** Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

**Skin contact** Wash off with warm water and soap.

<b>Inhalation</b>	If symptoms develop move victim to fresh air. Call a physician if symptoms develop or persist.
<b>Ingestion</b>	Call a physician immediately.
<b>Notes to physician</b>	Symptoms may be delayed.

## 5. Fire Fighting Measures

<b>Flammable properties</b>	Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard.
<b>Extinguishing media</b>	
<b>Suitable extinguishing media</b>	Alcohol foam. Dry chemical. Carbon dioxide (CO <sub>2</sub> ). Do not use water jet.
<b>Protection of firefighters</b>	
<b>Protective equipment and precautions for firefighters</b>	In case of fire and/or explosion do not breathe fumes. Containers should be cooled with water to prevent vapor pressure build up.

## 6. Accidental Release Measures

<b>Methods for containment</b>	Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk.
<b>Methods for cleaning up</b>	Should not be released into the environment. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

## 7. Handling and Storage

<b>Handling</b>	Pressurized container: Do not pierce or burn, even after use. Do not smoke while using or until sprayed surface is thoroughly dry. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not re-use empty containers. Do not get this material in contact with eyes. Avoid contact with skin. Avoid prolonged exposure.
<b>Storage</b>	Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Do not handle or store near an open flame, heat or other sources of ignition. Avoid exposure to long periods of sunlight. Store in cool place. Keep in an area equipped with sprinklers. Keep out of the reach of children. Keep away from food, drink and animal feedingstuffs. Level 3 Aerosol.

## 8. Exposure Controls / Personal Protection

### Exposure limits

#### ACGIH

Components	CAS #	TWA	STEL	Ceiling
n-Butane	106-97-8	1000 ppm	Not established	Not established
Isopropyl Alcohol	67-63-0	200 ppm	400 ppm	Not established
Propane	74-98-6	1000 ppm	Not established	Not established
Butylated Hydroxytoluene	128-37-0	2 mg/m <sup>3</sup>	Not established	Not established

#### OSHA

Components	CAS #	TWA	STEL	Ceiling
Isopropyl Alcohol	67-63-0	400 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established

### Personal protective equipment

<b>Eye / face protection</b>	Do not get in eyes. Chemical goggles are recommended.
<b>Skin protection</b>	Wear appropriate chemical resistant clothing. Chemical resistant gloves.
<b>Respiratory protection</b>	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

## 9. Physical & Chemical Properties

<b>Appearance</b>	Compressed liquefied gas.
<b>Boiling point</b>	188.6 °F (87.2 °C) estimated
<b>Color</b>	Clear. Colorless.
<b>Density</b>	0.6676 g/cm <sup>3</sup> estimated
<b>Flammability (HOC)</b>	36.2564 kJ/g estimated
<b>Flash back</b>	Yes
<b>Flash point</b>	-156 °F (-104.4 °C) Propellant
<b>Form</b>	Aerosol.
<b>Freezing point</b>	Not available
<b>Odor</b>	Characteristic.
<b>pH</b>	Not applicable
<b>Physical state</b>	Liquid.
<b>Pressure</b>	43 - 53 psig @ 70F
<b>Solubility</b>	Partially
<b>Specific gravity</b>	0.6677 estimated

## 10. Chemical Stability & Reactivity Information

<b>Chemical stability</b>	Risk of ignition.
<b>Conditions to avoid</b>	Heat, flames and sparks.

## 11. Toxicological Information

<b>Acute effects</b>	Acute LD50: 6343 mg/kg estimated, Rat, Dermal Acute LC50: 25 mg/l/4h estimated, Rat, Inhalation
----------------------	--

### Component analysis - LD50

#### Toxicology Data - Selected LD50s and LC50s

Aliphatic Petroleum Solvent	64742-89-8	Oral LD50 Mouse 5000 mg/kg; Dermal LD50 Rabbit 3000 mg/kg
Butylated Hydroxytoluene	128-37-0	Oral LD50 Rat 890 mg/kg
Isopropyl Alcohol	67-63-0	Inhalation LC50 Rat 72.6 mg/L 4 h; Oral LD50 Rat 4396 mg/kg; Dermal LD50 Rat 12800 mg/kg; Dermal LD50 Rabbit 12870 mg/kg
n-Butane	106-97-8	Inhalation LC50 Rat 658 mg/L 4 h
Propane	74-98-6	Inhalation LC50 Rat 658 mg/L 4 h
Synthetic Isoparaffinic Hydrocarbon	64742-47-8	Inhalation LC50 Rat >5.2 mg/L 4 h; Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rabbit >2000 mg/kg

## 12. Ecological Information

<b>Ecotoxicity</b>	Components of this product have been identified as having potential environmental concerns.  LC50 43.17 mg/L estimated, Fish, 96.00 Hours, EC50 3378 mg/L estimated, Daphnia, 48.00 Hours, IC50 65.4 mg/L estimated, Algae, 72.00 Hours,
--------------------	--

## 13. Disposal Considerations

<b>Waste codes</b>	D001: Waste Flammable material with a flash point <140 F
<b>Disposal instructions</b>	Contents under pressure. Dispose of this material and its container to hazardous or special waste collection point. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable waste, D001.

## 14. Transport Information

### Department of Transportation (DOT) Requirements

#### Basic shipping requirements:

Proper shipping name	Consumer commodity
Hazard class	ORM-D
Subsidiary hazard class	None

#### Additional information:

Packaging exceptions	156, 306
Packaging non bulk	156, 306
Packaging bulk	None

### IMDG

#### Basic shipping requirements:

Proper shipping name	AEROSOLS
Hazard class	2.1
UN number	1950

#### Additional information:

Packaging exceptions	LTD QTY
Labels required	None



### IATA

#### Basic shipping requirements:

Proper shipping name	Aerosols, flammable
Hazard class	2.1
UN number	1950

#### Additional information:

Packaging exceptions	LTD QTY
Labels required	None



## 15. Regulatory Information

### US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### U.S. - CERCLA/SARA - Section 313 - Emission Reporting

Isopropyl Alcohol	67-63-0	1.0 % de minimis concentration (only if manufactured by the strong acid process, no supplier notification)
-------------------	---------	--

### Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical Yes

### CERCLA (Superfund) reportable quantity

None

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 302 extremely hazardous substance	No
Section 311 hazardous chemical	Yes
Hazard categories (311/312)	Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

## Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of New and Existing Chemicals (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

## State regulations

### U.S. - Pennsylvania - RTK (Right to Know) List

Aliphatic Petroleum Solvent	64742-89-8	Present
Butylated Hydroxytoluene	128-37-0	Present
Isopropyl Alcohol	67-63-0	Environmental hazard
n-Butane	106-97-8	Present
Propane	74-98-6	Present
Synthetic Isoparaffinic Hydrocarbon	64742-47-8	Present

## 16. Other Information

### Further information

HMIS® is a registered trade and service mark of the NPCA.

### HMIS® ratings

Health: 1\*  
Flammability: 4  
Physical hazard: 0

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and experience currently available.

### MSDS sections updated

Product and Company Identification: Product and Company Identification  
Composition / Information on Ingredients: Ingredients  
Physical & Chemical Properties: Physical & Chemical Properties

### Prepared by

Regulatory Compliance