

SAFETY DATA SHEET

Clear Gel - #Y9Q

SDS No. B0028

Date: 7/22/22

Section 1 – Identification of the Mixture and Supplier

Product Name: CLEAR GEL - #Y9Q

SDS Number: B0028

CAS Number: Mixture – Not Established

Product Description: Non-Abrasive Cleaner for Printing Equipment Rollers

Manufacturer/Supplier: Burnishine Graphic Products, 25392 W. Park Court, Lake Villa, IL 60046,

Phone: 847-356-0222, FAX 847-306-3550, WORK HOURS 8-5 CST

EMERGENCY PHONE NUMBER (INFOTRAC) 800-535-5053 or 352-323-3500.

Section 2 – Hazard Identification

GHS Classification of the Substance or Mixture

Skin Irritant – Category 2 Eye Irritant – Category 2A Acute Toxicity/Oral- Category 4 Acute Toxicity/Inhalation – Category 5 Carcinogenicity – Category 2 Specific Target Organ Toxicity Single Exposure – Category 3 Specific Target Organ Toxicity Repeated Exposure – Category 2	None Known	Flammable Liquid- Category 4
---	------------	---------------------------------

GHS Label Elements



Signal Word: Warning

Hazard Statements:

H200s = Physical H300s = Health H400s = Environmental

- H227 Combustible liquid
- H302 Harmful if swallowed
- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H333 May be harmful if inhaled
- H336 May cause drowsiness or dizziness
- H351 Suspected of causing cancer
- H373 Causes damage to organs through prolonged or repeated exposure

HMIS

Health -2
Fire -2
React -0

PPE† Sec.8

Precautionary Statements:

P100s=General P200s = Prevention P300s = Response P400s = Storage P500s = Disposal

- P102 Keep out of reach of children
- P201 Obtain special instructions before use
- P202 Do not handle until all safety precautions have been read and understood
- P210 Keep away from heat/sparks/open flames/hot surfaces-No Smoking
- P243 Take precautionary measures against static discharge
- P260 Do not breath dust/fumes/gas/mists/vapors/or spray
- P264 Wash hands thoroughly after handling
- P270 Do not eat/drink/or smoke when using this product
- P271 Use only in a well ventilated area
- P280 Wear protective gloves/clothing/and eye/face protection
- P281 Use personal protective equipment as required
- P301+312 If swallowed: call a poison center or doctor/physician if you feel unwell/rinse mouth with plenty of water
- P302+352 If on skin: wash with plenty of soap and water
- P308+313 If exposed and concerned: get medical advice /attention
- P314 Get medical advice/attention if you feel unwell
- P332+313 If skin irritation occurs: get medical advice/attention
- P362 Take off contaminated clothing and wash before reuse
- P305+351+338 If in eyes: rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337+313 If eye irritation persist: get medical advice/attention

- P304+340 If inhaled: if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P304+312 If inhaled: call a poison center or doctor/physician if you feel unwell
- P370+378 In case of fire use water spray/dry chemical/carbon dioxide/alcohol foam
- P403+233 Store in a well-ventilated place. Keep container tightly closed
- P403+235 Store in well-ventilated place/keep cool
- P405 Store locked up
- P501 Dispose of contents/containers according to local regulations

Section 3 – Composition / Information on Ingredients

Ingredient Name	CAS No.	% WT.
Water	7732-18-5	46-65
Ethylene Glycol Monobutyl Ether	111-76-2	4-7
Ethylene Glycol	107-21-1	3-6
Diacetone Alcohol	123-42-1	1-2
Petroleum Distillate	8042-47-5	18-25
Kaolin	92704-41-1	4-7
Oleic Acid	112-80-1	5-9
Petrolatum	8009-03-8	3-6
Polyethylene Glycol Mono Ether	9036-19-5	2-3

Section 4 – First Aid Measures

Inhalation: Nasal irritation, nausea, dizziness, coughing, headache, shortness of breath, weakness, discoloration of face. Remove person from source of exposure to fresh air and keep at rest in a position comfortable for breathing. Administer oxygen if breathing is difficult. Give artificial respiration if person is not breathing. **GET MEDICAL ATTENTION IMMEDIATELY.**

Skin Contact: Itching, redness or burning of skin. Immediately flush skin thoroughly with plenty of water for several minutes and then wash skin with soap and water. Remove contaminated clothing and wash before reuse. If skin irritation persists, **GET IMMEDIATE MEDICAL ATTENTION.**

Eye Contact: Eye irritation. Immediately flush eyes with a directed stream of water for at least 15 minutes, forcibly holding eyelids apart to ensure complete irrigation of all eye and lid tissue. Remove contact lenses if present and easy to do. Continue Rinsing. If eye irritation persists, **GET IMMEDIATE MEDICAL ATTENTION.**

Ingestion: Irritation of the mouth and throat. Abdominal pain and nausea. Do not induce vomiting. If person is conscious, rinse mouth or give them a glass of water. If person is drowsy or unconscious and vomiting, place on the left side with head down. **GET MEDICAL ATTENTION IMMEDIATELY.**

Note to Physicians: Treat Symptoms

Special Precautions/Procedures: After first-aid, get appropriate in-plant, paramedic, or community medical support.

See Section 11 for more detailed information on health effects and symptoms.

Section 5 – Fire-Fighting Measures

Extinguishing Media: Water spray, dry chemical, carbon dioxide, alcohol foam.

Unusual Fire or Explosion Hazards: This product contains combustible organic compounds creating possible ignitable vapors when containers are heated. Heated vapors may be ignited by flames or sparks.

Hazardous Combustion Products: Combustion of can produce toxic gases (oxides of nitrogen) product may react with some metals (Aluminum, Zinc, Tin) to release hydrogen gas.

Fire-Fighting Instructions: Combustible liquid. Extinguish all sources of ignition. Keep away from heat, sparks and flames. Use extinguishing media appropriate for surrounding fire. Use water spray to cool nearby containers and structures exposed to fire. Do not release runoff from fire control methods into sewers or waterways. Keep personnel removed and upwind.

Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode with full protective clothing.

NFPA

**Health-2
Fire-2
React-0**

**Hazards:
Combustible**

Section 6 – Accidental Release Measures

Personal Precautions: Wear appropriate personal protective equipment as conditions warrant.(Review Section8) Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Follow all precautions for handling spill (Review Section7). Isolate spill or leak area and deny entry of untrained personnel.

Emergency Procedures: Isolate spill or leak. Eliminate all ignition sources. No smoking, flares, sparks, or flames in spill area. Ventilate spill area if fumes are present, keep unauthorized personnel away. Stay up-wind of any fumes.

Spill/Leak Containment and Cleanup: All equipment used when handling the spill must be grounded or non-sparking tools. Stop leak if you can do it without risk. Small spills: take up with sand or other non-combustible absorbent material and place into approved containers for later disposal. Large Spills: dike area with non-combustible absorbent material to contain spill. Prevent spill from entering sewers, waterways, or low areas. Transfer spilled liquid and diking material to suitable approved containers for recovery or disposal. Do not flush spilled material into a sewer. Neutralize remaining spilled material with a diluted solution of acid if the spilled material is an alkaline or diluted solution caustic if the spill material is acidic. Clean up residue with soap and water. Do not flush to sewer or waterways. Prevent release to the environment.

Refer to Section 13 for Proper Disposal of Spilled Material.

Regulatory Requirements: Any environmental release of a material that could cause harm to people or to the environment must be reported immediately to the National Response Center (NRC) and to appropriate state and local agencies.

Section 7 – Handling and Storage

Handling Precautions: This is a combustible product and should be used with caution. Do not get in eyes, on skin or on clothing. Harmful if inhaled, absorbed through skin or swallowed. Prevent possible eye and skin contact by wearing the recommended protective clothing and equipment. Wash thoroughly after handling. Remove contaminated clothing after use. Do not breath vapors or mists; use with adequate ventilation. Do not ingest. Do not cut, grind, puncture, drill or weld on or near containers. Take precautionary measures against static discharge. Keep containers closed when not in use. Do not use pressure to empty containers. Always loosen closure cautiously when opening. Vapors are combustible to open flames. Use in an area that will allow for evaporation or run off. Prevent soil contamination and entry into storm and floor drains, streams and into any body of water.

Storage Requirements: Combustible liquid. Store in a cool, dry, well-ventilated area away from direct sunlight, heat, flames, and sparks in a controlled environment. Do not store in temperatures exceeding 120°F. Do not store near combustible materials or liquids. Take precautionary measures against static discharge. Do not store in open, unlabeled or mislabeled containers. Empty containers retain product vapor and residue. Follow all label warnings even after container is empty. Keep from freezing. Keep out of reach of children.

Section 8 – Exposure Controls / Personal Protection

Exposure Limits / Guidelines Ingredient Name	OSHA PEL	ACGIH TLV
Water	None Estab.	None Estab.
Ethylene Glycol Monobutyl Ether	50 ppm	20 ppm
Ethylene Glycol	125 mg/m ³	100 me/m ³
Diacetone Alcohol	50 ppm	50 ppm
Petroleum Distillate	None Estab.	5 mg/m ³
Kaolin	5 mg/m ³	2 mg/m ³
Oleic Acid	None Estab.	None Estab.
Petrolatum	None Etab.	None Estab.
Polyethylene Glycol Mono Ether	None Estab.	None Estab.

Engineering Controls for Ventilation: Ensure good general ventilation. Use local exhaust ventilation to draw spray, mists, and vapors away from work area to prevent inhalation of product fumes. Provide general or local exhaust ventilation systems using corrosive resistant materials to maintain airborne contaminants below any recommended or standard occupational exposure limits. Local exhaust ventilation is preferred because it prevents contamination dispersion into the work area by controlling it at its source. Ventilation guidelines may be found in OSHA Regulations (29 CFR 1910.94) or in publications such as: American Conference of Governmental Industrial Hygienist.

PERSONAL PROTECTIVE EQUIPMENT

Respiratory Protection: If using in a confined area and fumes are present, use a respirator. None required under normal conditions of use if maintaining airborne contaminant concentrations below standard occupational exposure limits. Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear a MSHA/NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. For emergency or non-routine operations (cleaning spills, reactor vessel, or storage tanks) wear an SCBA. **Warning! Air-purifying respirators do not protect workers in oxygen-deficient environments.** If respirators are used, OSHA requires a written respiratory protection program that includes at least: medical certification, training, fit-testing, periodic environmental monitoring, maintenance, inspection, cleaning, and convenient, sanitary storage areas.

Eye Protection: Wear chemical safety goggles per OSHA eye and face protection regulations (29 CFR 1910.133). Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses. Have an eye wash station available where eye contact can occur.

Skin Protection: Wear chemically protective gloves impervious to conditions of use. Use neoprene, nitrile, or butyl type rubber gloves. Additional protection may be necessary to prevent skin contact, including use of apron, face shields, boots, or full body protection. A safety shower should be located in the general work area.

General Hygiene: Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Launder contaminated work clothes before reuse and keep personal protective equipment clean.

Section 9 – Physical and Chemical Properties

Appearance: Creamy Liquid

Odor: Slight Solvent Odor

pH: 6.5-7.5

Freeze Point: Estimated at 10°F (-12°C)

Boiling Point: Estimated at 212°F (100°C)

Odor Threshold: Not Determined

Vapor Pressure: Not Determined

Vapor Density (Air=1): Not Determined

Specific Gravity (H₂O=1, at 72 °F(22°C): .96

Flash Point: Estimated at 160°F

Upper/Lower Flammability: Not Determined

Auto Ignition Temp: Not Determined

Evaporation Rate (Water=1): Not Applicable

Partition Coefficient, N-Octanol/Water: Not Determined

Decomposition Temp: Not Determined

Viscosity: 5,000-10,000 cps at 72°F SP# 4 at 10rpm

VOC Content: 10.0% 96g/l .80Lb/Gal

Section 10 – Stability and Reactivity

Reactivity: No dangerous reactions known under normal conditions of use.

Chemical Stability: Stable in a controlled environment away from direct sunlight and stored at ambient temperatures.

Hazard Reactions: Hazardous reactions will not occur.

Conditions to Avoid: Combustible liquid. Avoid excessive heat or storing product in elevated temperatures or near heat, sparks, open flames or ignition sources. Reactive to the following metals: tin, aluminum, zinc, and brass.

Incompatible Materials: Strong oxidizers, acids, alkali and reducing agents.

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, and other toxic gases.

Section 11 – Toxicology Information

*Specific tests have not been conducted on this product. Our evaluations based on information from similar products, the ingredients and technical literature. Data for this material has been used to estimate the symptoms and effects of exposure.

Eyes

Eye contact with liquid or mists can cause severe irritation with corneal injury. Which may result in temporary impairment of vision.

Skin

Skin LD50: Not Established/ No Data

Brief contact may cause irritation to the skin. Prolonged contact may cause moderate skin irritation resulting in local redness. This product is not known to be a sensitizer.

Inhalation

Inhalation LC50: Not Established/ No Data

The product is expected to present a significant inhalation hazard if work area is properly ventilated. Inhalation of vapors, mists, or fumes will cause irritation of respiratory tract creating headaches, nausea, weakness, drowsiness and dizziness. Prolonged inhalation can cause organ damage.

Ingestion**Oral LD50: Not Established/ No Data**

Ingestion is not regarded as significant health hazard likely to arise from normal use. Ingestion will cause severe irritation of mouth, throat, and digestive tract. Severe abdominal pain, nausea, vomiting, and lethargy will likely occur, aspiration hazard.

Chronic Toxicity

The product does contain ingredients, or which are derived from components, that potentially may affect the following target organs: eyes, skin, respiratory system, liver, kidney, and central nervous system. Over exposure; suspect cancer hazard. May cause target organ damage of liver, kidneys, and central nervous system.

Carcinogenicity

IARC, NTP, and OSHA do list a few of the ingredients as a possible carcinogen: ACGIH lists Kaolin(92704-41-1) as a Category 2 carcinogen and Triethanolamine as an A3 confirmed animal carcinogen with unknown relevance to humans.

Mutagenicity

There are no reports of mutagenic effects attributable to the use of this type of product or from its ingredients.

Reproductive Toxicity

Possible reproductive hazards attributable to the use of this type of product or from its ingredients. Ingredient Ethylene Glycol (107-21-1) has caused teratogenic and fetotoxic effects in rats and mice.

Section 12 – Ecological Information

***Specific tests have not been conducted on this product. Our evaluation is based on information from similar products, the ingredients and technical literature. This information should be used only for a small truck spill and not meant to address discharges to sewers or treatment plants. Data for this material has been used to estimate its environmental impact.**

Toxicity: This material has a high potential for toxicity. Moderate biochemical oxygen demand and high potential to cause oxygen depletion in aqueous systems. A high potential to affect aquatic organisms.

Environmental Degradation: This product is readily biodegradable when diluted with large amounts of water, this material released into the environment is not expected to have a significant impact. (Minimum of 50 parts water to 1 part product). A moderate potential to persist in the environment.

Soil Absorption/ Mobility: This material is expected to be mobile in soil and not expected to absorb to suspended solids or sediments in water. A moderate potential to affect plant life.

Section 13 – Disposal Considerations

Waste Disposal Methods: As sold, this product when discarded or disposed of is a non-hazardous waste. The transportation, storage, treatment, and disposal of this waste material must be conducted in compliance with (40CFR 261, 262, 263, 264, 268, and 270). Do not discharge this material into lakes, streams, ponds, or other waters. Do not discharge this material into sewer systems without the approval from local sewage treatment plant authority. Care must be taken to prevent environmental contamination from the use of this material. If material is not approved to be discharged into sewer system, contact a licensed waste management contractor for detailed recommendations for disposal. Follow all applicable Federal, state, and local regulations. This non-hazardous liquid can be incinerated if it meets all OSHA and EPA regulations. Incinerate at a licensed waste disposal site with approved environmental authority. If this product is altered, it is the responsibility of the user to determine whether the material meets the criteria for hazardous waste at the time of disposal.

Disposal Regulatory Requirements: Follow applicable NRC, CERCLA, SARA, and RCRA regulations.

Container Cleaning and Disposal: Prior to cleaning or disposing of container, use caution when handling empty container (possible combustible vapors). Do not use pressure to empty containers. Empty containers retain product vapors or residue that could be combustible. Follow all label warnings even after container is empty. Do not cut, weld, braze, solder, drill, grind, or expose empty containers to heat, flames or other sources of ignition. Follow applicable Federal, state, and local OSHA and EPA regulations.

Section 14 – Transportation Information

Domestic US Road Transportation DOT (49 CFR 172.101):

Not Regulated as a Hazardous Material or Dangerous Goods.

Canadian Road Transportation (TDG):

Review Canadian Road Transportation (TDG) to determine if this product, for the packaging sizes being shipped, is considered dangerous goods. If this product is considered dangerous goods it may only require special labeling and proper shipping description.

Ocean Transportation (IMO/IMDG) (49 CFR 172.101):

Review Ocean Transport Regulations to determine if this product for the packaging sizes being shipped is considered dangerous goods. If this product is considered dangerous goods it may only require special labeling and a proper shipping description.

Air Transportation (ICAO/IATA) (49 CFR 172.101):

Review Air Transportation Regulations to determine if this product for the packaging sizes being shipped is considered dangerous goods. If this product is considered dangerous goods it may only require special labeling and a proper shipping description.

Section 15 – Regulatory Information

U.S. Federal Regulations

Toxic Substance Control Act (TSCA) Inventory Status:

The components for this product are on the TSCA Inventory or are exempt from TSCA Inventory Requirements.

Super Fund Amendments & Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (40 CFR 355):

Components:	Concentration:
Ethylene Glycol (107-21-1)	
Ethylene Oxide (75-21-8)	Trace Amounts

Section 311/312 Hazard Class (40 CFR 370):

Immediate Hazard: Yes
 Delayed Hazard: Yes
 Fire Hazard: Yes
 Pressure Hazard: No
 Reactive Hazard: No

Section 313 Toxic Chemicals (40 CFR 372):

Components:	Reporting Threshold:
Glycol Ether EB (111-76-2)	
Ethylene Glycol (107-21-1)	
Diethanolamine (111-42-2)	

Comprehensive Environmental Response and Liability Act (CERCLA):

Section 304 Hazardous Substances (40 CFR 302):

Components	Reporting Qty:
Ethylene Glycol (107-21-1)	
Ethylene Oxide (75-21-8)	Trace Amounts
Diethanolamine (111-42-2)	

OSHA Air Contaminants Standard (20 CFR 1910.1000):

The following components of this product are listed as having limits for air contaminants:

Glycol Ether EB (111-76-2)
1,4 Dioxane (123-91-1)
Ethylene Glycol (107-21-1)
Diacetone Alcohol (123-42-2)

State Regulations**California Proposition 65:**

The product contains the following chemicals known to State of California to cause cancer or birth defects based on maximum impurity levels of components:

1,4 Dioxane (123-91-1) Trace Amounts
Ethyl Acrylate (140-88-5) Trace Amounts
Ethylene Oxide (75-21-8) Trace Amounts
Titanium Dioxide(13463-67-7) Trace Amounts
Ethylene Glycol (102-21-1) Trace Amounts

Pennsylvania, Massachusetts & New Jersey Hazardous Substance List Right to Know:

The following components in the product are listed as hazardous at levels which require reporting:

Gylcol Ether EB (111-76-2)
Ethylene Glycol (107-21-1)
Oleic Acid (112-80-1)

International Regulations**Canadian Environmental Protection Act (CEPA):**

The components for this product are included on the Canadian Domestic Substances List. (DSL)

Canadian Workplace Hazardous Materials Information System (WHIMS):

Class D2B – Skin/ Eye Irritation – Reversible Damage
Class B3- Combustible Liquid Flashpoint 180°F

Section 16 – Other Information

Prepared by: SDS Coordinator

Revision Date: 7/22/22

Disclaimer: This safety data sheet and the information it contains is offered to you in good faith as a guide to the safe use of the product and believed to be accurate to the best of our knowledge. Not all information in this data sheet is supported by specific testing and the evaluations are based on information from similar products, the ingredients, and technical literature. The data contained herein is provided for your guidance only when handling the specific material designated in this SDS and does not relate to any process or to use with any other materials. We recommend testing to determine the suitability of this product for your particular purpose prior to use. No responsibility is accepted that the information is sufficient, correct, and complete in all circumstances, as to the safety and health of individuals, disposal of materials and protection of the environment. It is the user's obligation to consider this SDS as a supplement to the other information required to make an independent determination to assure compliance to applicable laws and regulations when handling this material. The data in this document is provided without any representation or warranty expressed or implied regarding its accuracy or correctness. No warranty, either expressed or implied of merchantability or fitness or of any nature is made with respect to any product referred to herein. Manufacturer does not assume responsibility and expressly disclaims liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the products referred to herein. Manufacturer urges persons receiving this data to make their own determination as to the information's suitability and completeness for their particular application.

