

# SAFETY DATA SHEET

### 1. Identification

Product identifier	Dykem <sup>®</sup> High Purity Action Marker - Black		
Other means of identification			
Part Number	44404		
Synonyms	Hi Purity AM 33- Fine, and 44-Medium * FORMULA CODE: * Q404 (Black)		
Recommended use	Solvent based marker		
Recommended restrictions	None known.		
Manufacturer/Importer/Supplier	Manufacturer/Importer/Supplier/Distributor information		
Manufacturer			
Company name	ITW Pro Brands		
Address	805 E. Old 56 Highway		
	Olathe, KS 66061		
Country	(U.S.A.)		
	Tel: +1 800-443-9536		
In Case of Emergency	1-800-535-5053 (Infotrac)		

## 2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 3
Health hazards	Serious eye damage/eye irritation	Category 2A
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	

## Label elements



Signal word	Warning	
Hazard statement	Flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness.	
Precautionary statement		
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist/vapors. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/eye protection/face protection.	
Response	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use appropriate media to extinguish.	
Storage	Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.	
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.	
Hazard(s) not otherwise classified (HNOC)	None known.	
Supplemental information	None.	

## 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Diacetone Alcohol		123-42-2	50 - 60
Propylene Glycol Methyl Ether		107-98-2	20 - 30
4. First-aid measures			
nhalation	Remove victim to fresh air and keep at rest in center or doctor/physician if you feel unwell.	a position comfortable for bre	athing. Call a poison
Skin contact	Take off immediately all contaminated clothing attention if irritation develops and persists.	J. Rinse skin with water/showe	er. Get medical
Eye contact	Immediately flush eyes with plenty of water for present and easy to do. Continue rinsing. Get		
ngestion	Rinse mouth. Get medical attention if sympton		
Most important symptoms/effects, acute and delayed	May cause drowsiness or dizziness. Headache Symptoms may include stinging, tearing, redno		
ndication of immediate nedical attention and special reatment needed	Provide general supportive measures and treat immediately. While flushing, remove clothes we ambulance. Continue flushing during transport Symptoms may be delayed.	hich do not adhere to affected	d area. Call an
General information	Take off all contaminated clothing immediately material(s) involved, and take precautions to p before reuse.		
5. Fire-fighting measures			
Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemic	al powder. Carbon dioxide (C	02).
Jnsuitable extinguishing nedia	Do not use water jet as an extinguisher, as this	s will spread the fire.	
Specific hazards arising from he chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance of ignition and flash back. During fire, gases hazardous to health may be formed.		
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full pro	otective clothing must be wor	n in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe so without risk.	fumes. Move containers from	n fire area if you can
Specific methods	Use standard firefighting procedures and cons	ider the hazards of other invo	lved materials.
General fire hazards	Flammable liquid and vapor.		
6. Accidental release meas	sures		
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep peo ignition sources (no smoking, flares, sparks, o protective equipment and clothing during clear damaged containers or spilled material unless closed spaces before entering them. Local aut cannot be contained. For personal protection,	r flames in immediate area). An-up. Avoid breathing mist/vap wearing appropriate protective thorities should be advised if s	Vear appropriate oors. Do not touch /e clothing. Ventilate
Methods and materials for containment and cleaning up	Use water spray to reduce vapors or divert vap smoking, flares, sparks, or flames in immediat away from spilled material. Take precautionary non-sparking tools.	e area). Keep combustibles (	vood, paper, oil, etc.
	Large Spills: Stop the flow of material, if this is possible. Use a non-combustible material like and place into a container for later disposal. For	vermiculite, sand or earth to s	oak up the product
	Small Spills: Absorb with earth, sand or other for later disposal. Wipe up with absorbent mat remove residual contamination.		
	Never return spills to original containers for re-	use. For waste disposal, see	section 13 of the SI

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

### 7. Handling and storage

Precautions for safe handling	Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapors. Avoid contact with eyes. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

### 8. Exposure controls/personal protection

#### **Occupational exposure limits**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits Components	s for Air Contaminants (29 CFR 1910. Type	1000) Value
Diacetone Alcohol (CAS 123-42-2)	PEL	240 mg/m3
		50 ppm
US. ACGIH Threshold Lim	it Values	
Components	Туре	Value
Diacetone Alcohol (CAS 123-42-2)	TWA	50 ppm
Propylene Glycol Methyl Ether (CAS 107-98-2)	STEL	100 ppm
	TWA	50 ppm
US. NIOSH: Pocket Guide	to Chemical Hazards	
Components	Туре	Value
Diacetone Alcohol (CAS 123-42-2)	TWA	240 mg/m3
		50 ppm
Propylene Glycol Methyl Ether (CAS 107-98-2)	STEL	540 mg/m3
		150 ppm
	TWA	360 mg/m3
		100 ppm
logical limit values	No biological exposure limits noted f	for the ingredient(s).
oosure guidelines		
US - California OELs: Skin	designation	
Propylene Glycol Methy	l Ether (CAS 107-98-2) Can	be absorbed through the skin.
propriate engineering htrols	Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.	
	s, such as personal protective equipn	
Eye/face protection	Not normally needed. If contact IS lik	kely, safety glasses with side shields are recommended.
Skin protection Hand protection	Wear appropriate chemical resistant	t gloves.
Other	Wear appropriate chemical resistant	t clothing.
Respiratory protection		ain airborne concentrations below recommended exposure ceptable level (in countries where exposure limits have not birator must be worn.

Thermal hazards	Wear appropriate thermal protective clothing, when necessary.		
General hygiene	When using do not smoke. Always observe good personal hygiene measures, such as washi		

General hygiene considerations When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

### 9. Physical and chemical properties

-	-
Appearance	
Physical state	Liquid.
Form	Liquid.
Color	Black.
Odor	Aromatic.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	248 - 338 °F (120 - 170 °C)
Flash point	89.0 - 108.0 °F (31.7 - 42.2 °C)
Evaporation rate	< 1 (BuAc = 1)
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or expl	osive limits
Flammability limit - lower (%)	1 %
Flammability limit - upper (%)	12.6 %
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	> 1 (air = 1)
Relative density	> 1 @ 70°F
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
VOC	84.91%, 816 g/L
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive u
Chemical stability	Material is stable under normal condition

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the decomposition temperature. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong acids. Strong oxidizing agents.
Hazardous decomposition products	Carbon oxides.

## 11. Toxicological information

### Information on likely routes of exposure

Inhalation	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Diarrhea. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

#### Information on toxicological effects

Acute toxicity	Not expected to be acutely toxic.				
omponents Species		Test Results			
Diacetone Alcohol (CAS 123-42-2	?)				
Acute					
Dermal					
LD50	Rat	> 1900 mg/kg, 24 Hours			
Oral					
LD50	Rat	3000 mg/kg			
Propylene Glycol Methyl Ether (CAS 107-98-2)					
Acute					
Dermal	- /				
LD50	Rat	> 2000 mg/kg			
Inhalation					
LC50	Rat	55 mg/l, 4 Hours			
Oral					
LD50	Rat	> 2000 mg/kg			
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritat	ion.			
Serious eye damage/eye Causes serious eye irritation.					
Respiratory or skin sensitization					
Respiratory sensitization	Not a respiratory sensitizer.				
Skin sensitization	This product is not expected to cause skin sensitization.				
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.				
Carcinogenicity	Not classifiable as to carcinogenicity to humans.				
ACGIH Carcinogens	ACGIH Carcinogens				
	Propylene Glycol Methyl Ether (CAS 107-98-2) A4 Not classifiable as a human carcinogen. IARC Monographs. Overall Evaluation of Carcinogenicity				
Not listed.					
	ed Substances (29 CFR 1910.1001-1053)				
US. National Toxicology Pr	Not listed. US. National Toxicology Program (NTP) Report on Carcinogens				
Not listed.	<b></b>				
Reproductive toxicity	This product is not expected to cause reproductive	or developmental effects.			
Specific target organ toxicity - single exposure	May cause drowsiness or dizziness.				
Specific target organ toxicity - repeated exposure	Not classified.				
Aspiration hazard	Not an aspiration hazard.				
hronic effects Prolonged inhalation may be harmful.					

### 12. Ecological information

Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment. Species Test Results			
Components			Test Results	
Diacetone Alcohol (CAS 123-	42-2)			
Aquatic				
Fish	LC50	Bluegill (Lepomis macrochirus)	420 mg/l, 96 hours	
Persistence and degradability	No data is	available on the degradability of any ingre	dients in the mixture.	
Bioaccumulative potential				
Partition coefficient n-octar Diacetone Alcohol	nol / water (lo	-0.098		
Mobility in soil	Not establi	shed.		
Other adverse effects	None known.			
13. Disposal consideratio	13. Disposal considerations			
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations.			
Local disposal regulations	Dispose in accordance with all applicable regulations.			
Hazardous waste code	D001: Waste Flammable material with a flash point <140 F The waste code should be assigned in discussion between the user, the producer and the waste disposal company.			
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).			
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.			

## 14. Transport information

DOT	
UN number	UN1263
UN proper shipping name	Paint related material including paint thinning, drying, removing, or reducing compound
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	B1, B52, IB3, T2, TP1, TP29
Packaging exceptions	150
Packaging non bulk	173
Packaging bulk	242
ΙΑΤΑ	
UN number	UN1263
UN proper shipping name	Paint related material (including paint thinning or reducing compounds)
Transport hazard class(es)	
Class	3

UN number UN proper shipping name Transport hazard class(es)	UN1263 Paint related material (including paint thinning or reducing compounds)
Class	3
Subsidiary risk	-
Packing group	III
Environmental hazards	No.
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG		
UN number	UN1263	
UN proper shipping name	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid	
	lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)	
Transport hazard class(es)		
Class	3	
Subsidiary risk	-	
Packing group Environmental hazards	111	
	No.	
Marine pollutant EmS	F-E, <u>S</u> -E	
-	Read safety instructions, SDS and emergency procedures before handling.	
Transport in bulk according to	Not applicable.	
Annex II of MARPOL 73/78 and		
the IBC Code		
DOT		
FLAMMABLE LIQUID		
IATA; IMDG		
3		
15. Regulatory information		
US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.	
Toxic Substances Control A		
	ort Notification (40 CFR 707, Subpt. D)	
Not regulated.		
CERCLA Hazardous Substar	ace List (40 CER 302 4)	
Not listed.		
SARA 304 Emergency releas	e notification	
Not regulated.		
	d Substances (29 CFR 1910.1001-1053)	
Not listed.		
Superfund Amendments and Reauthorization Act of 1986 (SARA)		
SARA 302 Extremely hazard	ous substance	
Not listed.		
SARA 311/312 Hazardous chemical	Yes	
Classified hazard categories	Flammable (gases, aerosols, liquids, or solids) Serious eye damage or eye irritation Specific target organ toxicity (single or repeated exposure)	

#### SARA 313 (TRI reporting) Not regulated.

#### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Contains component(s) regulated under the Safe Drinking Water Act.

(SDWA) **US state regulations** 

### US. New Jersey Worker and Community Right-to-Know Act

Diacetone Alcohol (CAS 123-42-2) Propylene Glycol Methyl Ether (CAS 107-98-2)

#### **California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

#### US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Propylene Glycol Methyl Ether (CAS 107-98-2)

#### International Inventories

Country(s) or region	Inventory name On inv	entory (yes/no)*		
Australia	Australian Inventory of Chemical Substances (AICS)	Yes		
Canada	Domestic Substances List (DSL)	Yes		
Canada	Non-Domestic Substances List (NDSL)	No		
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes		
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No		
Europe	European List of Notified Chemical Substances (ELINCS)	No		
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes		
Korea	Existing Chemicals List (ECL)	Yes		
New Zealand	New Zealand Inventory	Yes		
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes		
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes		
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes		
*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)				

inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

Issue date	11-13-2020
Version #	01
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. ITW Pro Brands cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.