

# LITHCO MATERIAL SAFETY DATA SHEET

## SECTION I: PRODUCT IDENTIFICATION

**TRADE NAME** (as labeled) **FAST DRY WASH**

**MANUFACTURER'S NAME:** Lithco, Inc. • 9449 Jefferson Blvd. • Culver City, CA 90232-2913

**PHONE NUMBER FOR ADDITIONAL INFORMATION:** (310) 559-7770 or (800) 454-8426

**FAX NUMBER FOR ADDITIONAL INFORMATION:** (310) 559-6908 or (888) 454-8426

**EMERGENCY INFORMATION:** For chemical emergency, spill, leak, fire, exposure or accident call Infotrac, day or night, at (800) 535-5053.

**DATE PREPARED OR REVISED:** 7-5-02 (Replaces 2-3-98)

**PREPARED BY** (optional):

## SECTION II: HAZARDOUS INGREDIENTS

			EXPOSURE LIMITS		
Chemical Names	CAS Numbers	%	ACGIH TLV	OSHA PEL	OTHER
VM & P Naphtha	64742-89-8		300 ppm	300 ppm	N/A
Toluene	108-88-3		150 ppm	100 ppm	N/A

**HMIS RATING:** Health: 3 Fire: 3 Reactivity: 0 Personal protection: B

## SECTION III: PHYSICAL PROPERTIES

**VAPOR DENSITY (AIR = 1):** 3.77

**MELTING POINT/RANGE:** N.D.

**SPECIFIC GRAVITY:** 0.756

**BOILING POINT/RANGE:** 231 - 282 °F

**SOLUBILITY IN WATER:** 0 %

**EVAPORATION RATE (BuAc = 1):** 1.24

**VAPOR PRESSURE, mm Hg @ 20 degrees C.:** 25.1

**APPEARANCE AND ODOR:** Water white liquid, aromatic odor

**This product contains 100 % VOC by formulation. VOC = 6.31 LB/GAL or 756 GM/LITER.**

**This product is not photochemically reactive.**

## SECTION IV: FIRE AND EXPLOSION

**FLASH POINT, degrees F. (give method):** 40 TCC

**AUTO-IGNITION TEMPERATURE, degrees F.:** N.D.

**FLAMMABLE LIMITS IN AIR (VOLUME %), LOWER :** 1% **UPPER:** 7%

**FIRE EXTINGUISHING MATERIALS:**

WATER SPRAY: <b>XX</b>	FOAM: <b>XX</b>	CARBON DIOXIDE: <b>XX</b>	DRY CHEMICAL: <b>XX</b>	OTHER: <b>N/A</b>
------------------------	-----------------	---------------------------	-------------------------	-------------------

**SPECIAL FIRE FIGHTING PROCEDURES:** Fire fighting personnel should wear full bunker gear with NIOSH approved SCBA.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Cool exposed containers with water fog to prevent explosions.

*This form complies with and is essentially similar to OSHA Form 174 as specified in 29CFR 1910.1200 (Federal OSHA Hazard Communication Standard) and complies with requirements of CAL/OSHA.*

**SECTION V: HEALTH HAZARD INFORMATION**

**SYMPTOMS OF OVEREXPOSURE FOR EACH POTENTIAL ROUTE OF EXPOSURE**

**INHALED:** Vapors may cause irritation to nose, throat and respiratory tract. High vapor concentrations may result in CNS depression.

**CONTACT WITH SKIN OR EYES:** Severely irritating to eyes. Mild irritant to skin. Prolonged skin contact may cause drying of skin and dermatitis.

**ABSORBED THROUGH SKIN:** Prolonged exposure may cause slight absorption resulting in CNS depression.

**SWALLOWED:** May result in vomiting. Aspiration of vomitus into lungs must be avoided as even small amounts may result in aspiration pneumonitis.

**HEALTH EFFECTS OR RISKS FROM EXPOSURE (Explain in lay terms)**

**ACUTE:** Irritation as noted above. CNS depression may be evidenced by giddiness, headache, dizziness and nausea.

**CHRONIC:** Unconsciousness and death may occur. Aspiration pneumonitis may be evidenced by coughing, labored breathing and cyanosis (bluish skin).

**FIRST AID EMERGENCY PROCEDURES**

**EYE CONTACT:** Flush eyes for at least 15 minutes with running water while holding eyelids open. Get medical attention.

**SKIN CONTACT:** Remove contaminated clothing. Wash affected area with soap and water. Seek medical attention if irritation persists. Do not wear contaminated clothing until properly laundered.

**INHALED:** Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration or CPR if not breathing. Seek medical attention.

**SWALLOWED:** Do not induce vomiting. If vomiting occurs, keep head below hips to prevent aspiration into lungs. Get medical attention.

**SUSPECTED CANCER AGENT?**

**XXX** NO. THIS PRODUCT'S INGREDIENTS ARE NOT FOUND IN THE LISTS BELOW.

YES.  FEDERAL OSHA  NTP  IARC

California employers using CAL/OSHA regulated carcinogens must register with CAL/OSHA. The CAL/OSHA and Federal OSHA carcinogen lists are similar.

**CALIFORNIA PROP. 65 STATEMENT**

THIS PRODUCT CONTAINS TOLUENE, A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR CAUSE REPRODUCTIVE HARM.

**PRE-EXISTING MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** Pre-existing eye, skin and respiratory disorders may be aggravated.

**SECTION VI: REACTIVITY DATA**

**PRODUCT IS XXX STABLE \_\_\_\_\_ UNSTABLE**

**CONDITIONS TO AVOID:** Avoid contact with heat, sparks and open flame.

**INCOMPATIBILITY** (materials to avoid): Strong oxidizing agents, sources of ignition.

**HAZARDOUS DECOMPOSITION PRODUCTS, INCLUDING COMBUSTION:** Carbon monoxide, carbon dioxide and unburned hydrocarbons

**HAZARDOUS POLYMERIZATION \_\_\_\_\_ MAY OCCUR XXX WILL NOT OCCUR.**

**CONDITIONS TO AVOID:** None under normal product use.

**SECTION VII: SPILL, LEAK AND DISPOSAL PROCEDURES**

**SPILL RESPONSE PROCEDURES, INCLUDING EMPLOYEE PROTECTION:** Extinguish all sources of ignition. Contain spill. Wear SCBA for airborne concentrations above TLV. Use sparkproof tools during clean-up. Soak up with inert absorbent.

**PREPARING WASTES FOR DISPOSAL** (containers, neutralization, etc.): Place in non-leaking containers suitable for material and certified for transporting hazardous waste.

NOTE: DISPOSE OF ALL WASTES IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

**SECTION VIII: SPECIAL HANDLING INFORMATION**

**VENTILATION AND ENGINEERING CONTROLS:** Provide ventilation to keep airborne concentration below TLV.

**RESPIRATORY PROTECTION (TYPE):** NIOSH/MCA approved for organic vapors for concentrations above TLV.

**EYE PROTECTION (TYPE):** Splashproof chemical goggles.

**GLOVES (SPECIFY MATERIAL):** Neoprene, nitrile or PVC.

**OTHER CLOTHING AND EQUIPMENT:** Eyewash station and safety shower should be provided.

**WORK PRACTICES, HYGIENIC PRACTICES:** Wash hands thoroughly after use and before eating, drinking, smoking or using the toilet.

**OTHER HANDLING AND STORAGE REQUIREMENTS:** Keep containers closed when not in use. Do not use near sources of ignition. Avoid prolonged or repeated contact with skin or breathing of vapors. Keep from children. For industrial use only.

**PROTECTIVE MEASURES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT:** Use protective gear as indicated above. Do not start electrical equipment in presence of vapors.

**SECTION IX: SHIPPING INFORMATION**

**FULL DOT SHIPPING NAME:** Compounds, cleaning liquid (Petroleum distillate, toluene)

**DOT HAZARD CLASS:** 3      **PACKING GROUP:** II      **UN/NA NUMBER:** NA 1993 Flammable liquid

---

**SECTION X: ENVIRONMENTAL STATEMENT**

**THIS PRODUCT IS SUBJECT TO REPORTING ACCORDING TO SARA, TITLE III (SUPERFUND AMENDMENT).**  
(RQ 20,000 lb. Hazardous Waste No. U220)

Information contained in this safety data sheet is drawn from recognized sources and is believed to be accurate and correct as of the date of issue. It is presented for your evaluation of the suitability of the product and for compliance with federal and state regulations. No claims are made for the accuracy, completeness and reliability of the information contained herein.