

MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Nikken Printing Supply U.S.A., Inc.

1117 Tower Road, Schaumburg, IL 60173, U. S. A.
Business Phone: (847) 885 - 1163 Fax: (847) 885 - 1932

Revision Date: 2/01/2007

24 HOUR EMERGENCY TELEPHONE NUMBER: 1-800-535-5053 INFOTRAC

PRODUCT TRADE NAME: CTP PLATE CLEANER

Product use: **Plate Cleaner & Scratch Remover for CTP Plates.**

2. COMPOSITION / INFORMATION ON INGREDIENTS:

Chemical Name	% by Wt Range	CAS Number	EXPOSURE LIMITS 8 hr. TWA (PPM)	
			OSHA PEL	ACGIH TLV
Distillate(petroleum), hydrotreated light	20.00-30.00	64742-47-8	N/D	N/D

3. HAZARDS IDENTIFICATION:

EMERGENCY OVERVIEW

Cloudy, white emulsion liquid with solvent odor. Caution! Irritant liquid and Vapor, Flash Point >93.5°C. HARMFUL IF SWALLOWED. Irritant liquid and vapor. May cause eye digestive, and respiratory tract irritation. Ingestion may cause central nervous system effects, cardiopulmonary effects and kidney effects. Symptoms include: Convulsions, acidosis, coma, irregular heart beat, heat and kidney failure. This product has caused adverse birth and reproductive effects. Target Organs: Central nervous system, kidneys, heart, respiratory systems.

HMIS HAZARD CLASS

HEALTH	(Blue)	1
FLAMMABILITY	(Red)	1
REACTIVITY	(Yellow)	0
PROTECTIVE EQUIPMENT		B

HAZARD INDEX:

0=Minimal Hazard 1=Slight Hazard 2=Moderate Hazard 3=Serious Hazard 4=Severe Hazard

POTENTIAL HEALTH EFFECTS

EYES: Exposure may cause eye irritation, stinging, tearing, redness, and swelling.

SKIN CONTACT: Exposure may cause skin irritation. Prolonged and repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking, skin burns, and skin damage.

INGESTION: May cause nausea and vomiting. Toxicity effects may include paralysis of eye muscles, convulsions, rapid heart beat, kidney abnormalities, and possible cardiac failure. This material can enter the lungs during swallowing or vomiting and cause lung inflammation and/or damage.

INHALATION: May cause respiratory tract irritation. Heated or misted substance may cause headache, irregular eye movements, and possible coma.

CHRONIC (CANCER) INFORMATION: May cause kidney injury. This product has not been identified as possible cancer hazard by NTP, IARC, or OSHA.

ACUTE EFFECTS: May cause skin, eye and digestive tract irritation.

OTHER HEALTH HAZARDS: None.

4. FIRST AID MEASURES:

EYES: Immediately flush eyes with water for at least 15 minutes, occasionally lifting the upper and lower lids. Get medical attention immediately. Do not allow victim to rub or keep eyes closed.

SKIN: Wash off in flowing water or shower for 15 minutes while removing contaminated clothing and shoes. Get medical help if irritation develops and persists. Remove contaminated clothing.

INGESTION: Do not induce vomiting. This material is an aspiration hazard. If individual is drowsy or unconscious, place on left side with the head down. Get medical attention.

INHALATION: Remove to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Get medical attention.

NOTE TO PHYSICIAN: Treat symptomatically and supportively.

5. FIRE FIGHTING MEASURES:

FLASH POINT: >93.5°C, TCC.

FLAMMABLE LIMITS, % Volume in air: LFL: 1.00 ; UFL: 15.00

EXTINGUISHING MEDIA: Use dry chemical. Water or foam may cause frothing.

FIRE FIGHTING INSTRUCTIONS: Firemen should wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment.

FIRE & EXPLOSION HAZARDS: This product is combustible and may be ignited by heat or flame.

6. ACCIDENTAL RELEASE MEASURES:

*****Large Spills***** Eliminate potential sources of ignition. Wear appropriate respirator and other protective clothing. Shut off source of leak only if it is safe to do so. Prevent from entering drains, sewer, streams or other bodies of water. Prevent from spreading. If runoff occurs, notify authorities as required. Pump or vacuum transfer spilled product to a non-leaking containers and seal tightly for proper disposal. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

CTP PLATE CLEANER

7. HANDLING AND STORAGE: Cause eye and skin irritation. Do not get in eyes, on skin, on clothing. Avoid ingestion and inhalation. Wash thoroughly after handling. Keep away from sources of ignition. "Empty containers retain product residue, (liquid and / vapor), and can be dangerous". Do not cut, weld, pressurize, braze, solder, grind, drill, or expose such containers to heat, sparks or open flames. Empty drums should be completely drained, properly bunged, and promptly returned and disposed of. Prevent build up of vapors to explosive concentration. Keep away from sources of ignition. Store in a tightly closed container. Store in a cool, dry, well-ventilated area away from incompatible substances. Use with adequate ventilation. Maintain good housekeeping. FOR INDUSTRIAL USE ONLY. "KEEP OUT OF REACH OF CHILDREN".

8. EXPOSURE CONTROLS, PERSONAL PROTECTION:

Engineering controls: Local exhaust ventilation may be necessary to keep airborne concentrations below the permissible exposure limits-SEE SECTION 2. Use explosion-proof ventilation as required to control vapor concentrations.

PERSONAL PROTECTIVE EQUIPMENT (PPE):

RESPIRATORY PROTECTION: Avoid prolonged or repeated breathing of vapors. If exposure may or does exceed occupational exposure limits (Sec. 2) use a NIOSH-Approved respirator to prevent overexposure. In accord with 29 CFR 1910.134. Use either an atmosphere-supplying respirator or an air-purifying respirator for organic vapors.

EYE PROTECTION: Use safety glasses or goggles as appropriate (29 CFR 1910.133).

SKIN: Wear solvent resistant gloves.

OTHER CLOTHING AND EQUIPMENT: It is suggested that a source of clean water be available in the work area for flushing eyes and skin. Impervious clothing should be worn as needed.

9. PHYSICAL AND CHEMICAL PROPERTIES:

Appearance: Cloudy, white emulsion liquid. Odor: Solvent odor. Boiling Point: N/D Vapor Density: >1
Solubility in Water: Insoluble Specific Gravity: N/D Density: 1.00-1.05g/cm3 pH: 1.0-1.3
Volatile Organic Content (VOC, EPA Method 24): N/D
VOC Composite Partial Pressure, mm Hg at 20°C: N/D
Photochemical Reactivity SCAQMD Rule 443: None Photochemically Reactive.

10. STABILITY AND REACTIVITY:

STABILITY: Stable at room temperature in closed containers under normal storage and handling conditions.

CONDITIONS TO AVOID: Ignition sources, open flame and excess heat.

HAZARDOUS POLYMERIZATION: Has not been reported.

INCOMPATIBILITY WITH OTHER MATERIALS: Strong oxidizing agents, silver-copper wire, acid and alkalis.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon dioxide, carbon monoxide, and various hydrocarbons.

11. TOXICOLOGICAL INFORMATION:

Table with 4 columns: Chemical Name, CAS Number, LC50 PPM (Inhalation rat), LD 50 mg/kg (Oral-rat). Row 1: Distillate(petroleum), hydrotreated light, 64742-47, N/A, N/A

12. ECOLOGICAL INFORMATION: On soil, ethylene glycol may leach to groundwater and biodegrade rapidly. In water, ethylene glycol readily biodegrades. Ethylene glycol is not expected to bioconcentrate in marine life.

13. DISPOSAL CONSIDERATIONS: Dispose in a manner consistent with federal, state, and local regulations. Refer to latest EPA or State Regulations regarding proper disposal.

14. TRANSPORT INFORMATION: This product is not hazardous material for (DOT) shipping.

D.O.T. SHIPPING description: Not Regulated.

IMO: SHIPPING NAME: Not Regulated.

IATA: SHIPPING NAME: Not Regulated

15. REGULATORY INFORMATION:

Table with 5 columns: Chemical Name, % by Wt Range, CAS Number, EXPOSURE LIMITS 8 hr. TWA (PPM) OSHA PEL, ACGIH TLV. Row 1: Distillate(petroleum), hydrotreated light, 20.00-30.00, 64742-47-8, N/D, N/D

16. OTHER INFORMATION: All information appearing herein is based upon Data obtained from Manufacturer and/or recognized technical sources. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the material are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use, disposal of the material. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for his own particular use. To the best of our knowledge, the information contained herein is accurate. However, neither Nikken Printing Supply U.S.A., nor any of its distributors assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.