

# **Material Safety Data Sheet - Black Diamond**

Date: 12-4-2000

	Н	M		S	
	Hazard Ratings				1
Minimal Slight	0	Serious Severe	3	Flammability	1
Slight Moderate	2	Severe	4	Reactivity	0

Material Safety and Data Sheet prepared by Gus Lindquist

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**DISTRIBUTOR:** Van Son Holland Ink Corporation of America

92 Union Street, Mineola, NY 11501

**Emergency Telephone:** 516-294-8811 **Product Class:** Offset Ink Non-oxidizing

Trade Name: Black Diamond

MANUFACTURER:

Van Son Royal Dutch Printing Ink Factories,

Hilversum, Holland

Chemtrec 24 Hour Emergency No-800-424-9300

Manufacturer's Code ID: VS154

## 2. INGREDIENT COMPOSITION INFORMATION

Ingredient	CAS No.	WT%	OSHA (PEL)	ACGIH (TLV)	Carcinogen
Carbon Black	1333-86-4	15-25	3.5 mg/M3	3.5 mg/M3	No
Organic Pigments	Various	2-10	3.5 mg/M3	3.5 mg/M3	No
Synthetic Resins	Various	30-50	N/A	N/Ă	No
Naphthenic Severe Hydrotreated					
Middle Distillate	64742-53-6	15-20	5mg/M3	N/A	No
Vegetable Oil Includes		20-30	N/A		
Linseed Oil	8001-26-1				
Soya Oil	8001-22-7				
Canolin Oil	8002-13-9				
Polymeric Wax Blend	N/A	2-5	N/A	N/A	No

## 3. HAZARDS IDENTIFICATION

#### 4. FIRST AID MEASURES

EEEECTS	ΩE	OVEREXPOSURE	
FFFF(.IS	l JF	UNEREXPUNIRE	

**Eye Contact**......Direct contact may cause irritation.

of nasal and respiratory passages.

**Ingestion**.....May cause gastrointestinal irritation.

Medical Conditions aggravated by normal exposure: Persons with dermatitis should avoid skin contact.

Target Organs: ......Skin, eyes, lungs.

Primary Routes of entry ......Eyes, inhalation, dermal.

#### EMERGENCY FIRST AID PROCEDURES

If irritation persists, contact a physician.

• Skin Contact: .......Wash with soap and water. Remove contaminated clothing and wash

thoroughly before reusing.

• Inhalation ......Remove individual to fresh air.

### **5. FIRE FIGHTING MEASURES**

Flash Point ......Above 250°F Method used: closed cup

**Explosion Limits**.....LEL: N/A UEL: N/A

Extinguishing Media......Foam, carbon dioxide, dry chemical. Water spray may be

applied to cool exposed closed containers.

Monoxide and Carbon Dioxide generated as combustion products.

**Special Fire Fighting Procedures**......Self-contained breathing apparatus recommended.

#### 6. ACCIDENTAL RELEASE MEASURES

**Procedure when material spilled or released:** Wipe up. Dispose of wipes in approved waste containers.

If petroleum hydrocarbon is used, provide sufficient ventilation.

Waste Disposal Method: Dispose of in accordance with Federal, State and Local regulations.

#### 7. HANDLING AND STORAGE

**Handling:** Avoid storage above 90° F. Keep containers closed when not in use.

Other Precautions: None required.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Ventilation:** Use sufficient ventilation. **Eye Protection:** Goggles recommended.

**Protective Gloves:** Gloves recommended. **Other Protection:** None required.

**Respiratory Protection:** None required.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Volatile Organic Compounds: (VOCs) 0.40 lbs./gallon 45 Grams/liter Method 24

Boiling Range °F:> 590°

Vapor Density vs. Air: Heavier

Freezing Point °F: N/A

Vapor Pressure: less than 0.04psi

Density: 9.0 lbs./ gallon ASTM D1475 Specific Gravity: 1.07
Type of Odor: Oily Odor Threshold: High

Appearance: Black viscous paste.

pH: N/A

Evaporation Rate vs. Butyl Acetate: Slower Coefficient of Water/oil Distribution: N/A

Percentage Volatile By Weight: 5% ASTM D2369

#### 10. STABILITY AND REACTIVITY

**Product Stability:** Stable

**Conditions to Avoid:** Strong oxidizing agents. Avoid storage above 90°F.

Keep containers closed when not in use.

Hazardous Decomposition Products: None. Hazardous Polymerization: Will not occur.

## 11. TOXICOLOGICAL INFORMATION

National Toxicology Program (NTP), or the International Agency for Research on

Cancer (IARC).

Mutagen No
Teratogen No
Reproductive Toxicity No

### 12. ECOLOGICAL INFORMATION

This product has not been evaluated, but there is no evidence to suggest it will cause any significant environmental problem.

## 13. DISPOSAL CONSIDERATIONS

**Material Released or spilled:** This product is not regulated under the Federal Resource Conservation and Recovery Act (RCRA) as a hazardous waste. State and/or local regulations may apply. Spill should be contained, absorbed with suitable absorbent material and placed in suitable containers for disposal in a licensed facility in accordance with Local, State and Federal laws. Do not discharge into waterways or sewer systems.

#### 14. TRANSPORT INFORMATION – DOT (HM 181): Not required – Shipping Labels: None required

#### 15. REGULATORY INFORMATION

TSCA (Toxic Substance Control Act)......All ingredients listed in TSCA Inventory CERCLA Superfund 40CFR 117.302......Contains no reportable materials

SARA Title III......None

FDA......This printing ink is not a food additive and would not have approval for

direct or indirect contact with food.

EINECS (European Economic Community)......All ingredients listed.

California Proposition 65......None

CONEG Legislation.......Meets all current State and Heavy Metal limitations.

Canadian WHMIS......Non-controlled product

**Vegetable Ink Printing Act of 1994** ......Meets the 20% minimum requirement of vegetable oil in sheet fed inks.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best of the knowledge of Van Son Holland Ink Corporation of America. The data on this sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The hazards covered are believed to be those most likely to occur in the reasonable or ordinary use of these materials. Van Son Holland Ink Corporation of America assumes no legal responsibility for use or reliance on this data.