

Material Safety Data Sheet – Quickson Signature Colors

Date 5/6/2003

	Н	M		S	
	Hazard Ratings			Health	1
Minimal	0	Serious	3	Flammability	1
Slight Moderate	1 2	Severe	4	Reactivity	0

Material Safety and Data Sheet prepared by W. DeBoer

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

DISTRIBUTOR: Van Son Holland Ink Corporation of America

92 Union Street, Mineola, NY 11501

Emergency Telephone: 516-294-8811
Product Class: Offset Ink, oxidizing
Trade Name: Quickson Signature Colors

MANUFACTURER: Van Son Royal Dutch Ink Factories

Hilversum, Holland

Chemtrec 24 Hour Emergency No-800-424-9300 Manufacturer's Code ID: VS9830, VS9831 VS9832

VS9835

2. INGREDIENT COMPOSITION INFORMATION

Ingredient	CAS No.	WT%	OSHA (PEL)	ACGIH (TLV)	Carcinogen
Organic Pigments	Various	15-25	3.5mg/M3	3.5mg/M3	No
Synthetic Resins	Various	20-40	N/A	N/A	No
Vegetable Oils includes:	8001-Various	8-18	N/A	N/A	No
Linseed Oil	8001-26-1				
Soya Oil	8001-22-7				
Severe Solvent Refined	64742-13-8				
and Acid Treated Middle Distillate	64741-91-9	20-40	N/A	N/A	No
Cobalt Drier	61789-52-4	0-1	0.1mg/M3	N/A	IARC
Manganese Drier	61788-58-7	0-1	5mg/M3	N/A	No
Polymeric Wax Blend	N/A	2-4	N/A	N/A	No

3. HAZARDS IDENTIFICATION

OSHA Hazard Communication 29 CFR 1910.1200Manganese compound

4. FIRST AID MEASURES

EFFECTS	OF	OVEREXPOSURE
---------	----	---------------------

Eye Contact.....Direct contact may cause irritation.

Skin ContactProlonged contact or repeated exposure may cause minor irritation.

of nasal and respiratory passages.

Ingestion......May cause gastrointestinal irritation.

Medical Conditions aggravated by normal exposure: Persons with dermatitis should avoid skin contact.

Target Organs:Skin, eyes, lungs.

Primary Routes of entryEyes, inhalation, dermal.

EMERGENCY FIRST AID PROCEDURES

If irritation persists, contact a physician.

• Skin Contact:Wash with soap and water. Remove contaminated clothing and wash

thoroughly before reusing.

5. FIRE FIGHTING MEASURES

Flash PointAbove 250°F Method used: closed cup

Explosion Limits.....LEL: N/A UEL: N/A

Extinguishing Media......Foam, carbon dioxide, dry chemical. Water spray may be

applied to cool exposed closed containers.

Unusual Fire and Explosion Hazards........................Dense smoke may be generated when burning. Carbon

Monoxide and Carbon Dioxide generated as combustion products.

Special Fire Fighting Procedures......Self-contained breathing apparatus recommended.

6. ACCIDENTAL RELEASE MEASURES

Procedure when material spilled or released: Wipe up. Dispose of wipes in approved waste containers.

If petroleum hydrocarbon is used, provide sufficient ventilation.

Waste Disposal Method: Dispose of in accordance with Federal, State and Local regulations.

7. HANDLING AND STORAGE

Handling: Avoid storage above 90° F. Keep containers closed when not in use.

Other Precautions: None required.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation: Use sufficient ventilation. **Eye Protection:** Goggles recommended.

Protective Gloves: Gloves recommended. **Other Protection:** None required.

Respiratory Protection: None required.

9. PHYSICAL AND CHEMICAL PROPERTIES

Volatile Organic Compounds: (VOCs) 2.10-2.30 lbs./gallon 240-260 Grams/liter Method 24

Vapor Density vs. Air: Heavier
Density: 8.5-8.85 lbs./ gallon ASTM D1475
Type of Odor: Oily

Vapor Pressure: less than 0.04psi
Specific Gravity: 1.00-1.05
Odor Threshold: High

Appearance: Colored viscous paste. **pH:** N/A

Evaporation Rate vs. Butyl Acetate: Slower Coefficient of Water/oil Distribution: N/A

Percentage Volatile By Weight: 23-27% ASTM D2369

10. STABILITY AND REACTIVITY

Product Stability: Stable

Conditions to Avoid: Strong oxidizing agents. Avoid storage above 90°F.

Keep containers closed when not in use.

Hazardous Decomposition Products: None. **Hazardous Polymerization:** Will not occur.

11. TOXICOLOGICAL INFORMATION

National Toxicology Program (NTP). International Agency for Research on Cancer (IARC)

classifies cobalt compounds as 2B carcinogens (possibly carcinogenic to humans)

MutagenNoTeratogenNoReproductive ToxicityNo

12. ECOLOGICAL INFORMATION

This product has not been evaluated, but there is no evidence to suggest it will cause any significant environmental problem.

13. DISPOSAL CONSIDERATIONS

Material Released or spilled: This product is not regulated under the Federal Resource Conservation and Recovery Act (RCRA) as a hazardous waste. State and/or local regulations may apply. Spill should be contained, absorbed with suitable absorbent material and placed in suitable containers for disposal in a licensed facility in accordance with Local, State and Federal laws. Do not discharge into waterways or sewer systems.

14. TRANSPORT INFORMATION- DOT (HM 181): Not required - Shipping Labels: None required

15. REGULATORY INFORMATION

TSCA (Toxic Substance Control Act)......All ingredients listed in TSCA Inventory

CERCLA Superfund 40CFR 117.302Contains no reportable materials

direct or indirect contact with food.

EINECS (European Economic Community)......All ingredients listed.

California Proposition 65......None

Canadian WHMIS......Controlled product

This information is furnished without warranty, expressed or implied, except that it is accurate to the best of the knowledge of Van Son Holland Ink Corporation of America. The data on this sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The hazards covered are believed to be those most likely to occur in the reasonable or ordinary use of these materials. Van Son Holland Ink Corporation of America assumes no legal responsibility for use or reliance on this data.

Prepared by W. DeBoer Date 5/6/2003