



Material Safety Data Sheet - Quickson Special Intense Black

Date: 2/26/2001

H		M		I		S	
Hazard Ratings							
Minimal	0	Serious	3	Health	1		
Slight	1	Severe	4	Flammability	1		
Moderate	2			Reactivity	0		

Material Safety and Data Sheet prepared by Gus Lindquist

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER: Van Son Holland Ink Corporation of America
92 Union Street, Mineola, NY 11501

Emergency Telephone: 516-294-8811

Product Class: Offset Black Ink Oxidizing

Trade Name: Quickson Special Intense Black

MANUFACTURER:

Van Son Royal Dutch Printing Ink Factories,
Hilversum, Holland

Chemtrec 24 Hour Emergency No-800-424-9300

Manufacturer's Code ID: VS9137, VS9127, VS9147

2. INGREDIENT COMPOSITION INFORMATION

Ingredient	CAS No.	WT%	OSHA (PEL)	ACGIH (TLV)	Carcinogen
Carbon Black	1333-86-4	15-30	3.5mg/M3	3.5mg/M3	No
Organic Pigments	See Table 2	2-10	3.5mg/M3	3.5mg/M3	No
Synthetic Resins	Various	20-40	N/A	N/A	No
Vegetable Oil Includes	Various	12-20	N/A	N/A	No
Linseed Oil	8001-26-1				
Soy Oil	8001-22-7				
Severe Acid Treated	64742-13-8				
or Solvent Refined Middle Distillate	64741-91-9	20-40	5mg/M3	N/A	No
Cobalt Drier	61789-52-4	0-1	0.1mg/M3	N/A	IARC
Manganese Drier	8030-70-4	0-1	5mg/M3	N/A	No
Polymeric Wax Blend	N/A	2-4	N/A	N/A	No

3. HAZARDS IDENTIFICATION

OSHA Hazard Communication 29 CFR 1910.1200Carbon Black, Manganese Compound

4. FIRST AID MEASURES

EFFECTS OF OVEREXPOSURE

- Eye Contact**Direct contact may cause irritation.
- Skin Contact**Prolonged contact or repeated exposure may cause minor irritation.
- Inhalation**Excess inhalation of mist or vapor may cause dizziness, nausea or irritation of nasal and respiratory passages.
- Ingestion**May cause gastrointestinal irritation.
- Medical Conditions aggravated by normal exposure:** Persons with dermatitis should avoid skin contact.
- Target Organs:**Skin, eyes, lungs.
- Primary Routes of entry**Eyes, inhalation, dermal.

EMERGENCY FIRST AID PROCEDURES

- **Eye Contact**Flush with large amounts of water until irritation subsides. If irritation persists, contact a physician.
- **Skin Contact:**Wash with soap and water. Remove contaminated clothing and wash thoroughly before reusing.
- **Ingestion**If swallowed, do not induce vomiting. Call a physician.
- **Inhalation**Remove individual to fresh air.

5. FIRE FIGHTING MEASURES

- Flash Point**Above 250°F Method used: closed cup
- Explosion Limits**LEL: N/A UEL: N/A
- Extinguishing Media**Foam, carbon dioxide, dry chemical. Water spray may be applied to cool exposed closed containers.
- Unusual Fire and Explosion Hazards**Dense smoke may be generated when burning. Carbon Monoxide and Carbon Dioxide generated as combustion products.
- Special Fire Fighting Procedures**Self-contained breathing apparatus recommended.

6. ACCIDENTAL RELEASE MEASURES

- Procedure when material spilled or released:** Wipe up. Dispose of wipes in approved waste containers. If petroleum hydrocarbon is used, provide sufficient ventilation.
- Waste Disposal Method:** Dispose of in accordance with Federal, State and Local regulations.

7. HANDLING AND STORAGE

Handling: Avoid storage above 90° F. Keep containers closed when not in use.
Other Precautions: None required.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation: Use sufficient ventilation. **Eye Protection:** Goggles recommended.
Protective Gloves: Gloves recommended. **Other Protection:** None required.
Respiratory Protection: None required.

9. PHYSICAL AND CHEMICAL PROPERTIES

Volatile Organic Compounds: (VOCs) 2.10 lbs./gallon	240 Grams/liter Method 24
Boiling Range °F: > 500°	Freezing Point °F: N/A
Vapor Density vs. Air: Heavier	Vapor Pressure: less than 0.04psi
Density: 8.78 lbs./ gallon ASTM D1475	Specific Gravity: 1.05
Type of Odor: Oily	Odor Threshold: N/A
Appearance: Black viscous paste.	pH: N/A
Evaporation Rate vs. Butyl Acetate: Slower	Coefficient of Water/oil Distribution: N/A
Percentage Volatile By Weight: 25% ASTM D2369	

10. STABILITY AND REACTIVITY

Product Stability: Stable
Conditions to Avoid: Strong oxidizing agents. Avoid storage above 90°F.
 Keep containers closed when not in use.
Hazardous Decomposition Products: None.
Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

CarcinogenContains no materials that are considered carcinogenic by OSHA or the National Toxicology Program (NTP). The International Agency for Research on Cancer (IARC) lists cobalt compounds and carbon black as possible human carcinogens (Class 2B.)
MutagenNo
TeratogenNo
Reproductive ToxicityNo

12. ECOLOGICAL INFORMATION

This product has not been evaluated, but there is no evidence to suggest it will cause any significant environmental problem.

13. DISPOSAL CONSIDERATIONS

Material Released or spilled: This product is not regulated under the Federal Resource Conservation and Recovery Act (RCRA) as a hazardous waste. State and/or local regulations may apply. Spill should be contained, absorbed with suitable absorbent material and placed in suitable containers for disposal in a licensed facility in accordance with Local, State and Federal laws. Do not discharge into waterways or sewer systems.

14. TRANSPORT INFORMATION- **DOT (HM 181) :** Not required – **Shipping Labels:** None required

15. REGULATORY INFORMATION

TSCA (Toxic Substance Control Act).....All ingredients listed in TSCA Inventory
CERCLA Superfund 40CFR 117.302.....Contains no reportable materials
SARA Title III.....2% Cobalt Compound and 2% Manganese Compound.
FDA.....This printing ink is not a food additive and would not have approval for direct or indirect contact with food.
EINECS (European Economic Community)All ingredients listed.
California Proposition 65.....None
CONEG Legislation.....Meets all current State and Heavy Metal limitations.
Canadian WHMIS.....Controlled product
Vegetable Ink Printing Act of 1994Meets the 20% minimum requirement of vegetable oil in sheet fed inks.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best of the knowledge of Van Son Holland Ink Corporation of America. The data on this sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The hazards covered are believed to be those most likely to occur in the reasonable or ordinary use of these materials. Van Son Holland Ink Corporation of America assumes no legal responsibility for use or reliance on this data.