

# Material Safety Data Sheet - Quickson Special Wax Free Black

Date: 12-5-2000

	Н	M		S	
Hazard Ratings			Health	1	
Minimal Slight	0	Serious Severe	3	Flammability	1
Moderate	2	Severe	4	Reactivity	0

Material Safety and Data Sheet prepared by Gus Lindquist

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**DISTRIBUTOR:** Van Son Holland Ink Corporation of America

92 Union Street, Mineola, NY 11501

Emergency Telephone: 516-294-8811 Product Class: Offset Ink Oxidizing

Quickson Special Wax Free Black Trade Name:

MANUFACTURER: Van Son Royal Dutch Printing Ink

Factories, Hilversum, Holland

Chemtrec 24 Hour Emergency No-800-424-9300

Manufacturer's Code ID: VS93310

#### 2. INGREDIENT COMPOSITION INFORMATION

Ingredient	CAS No.	WT%	OSHA (PEL)	ACGIH (TLV)	Carcinogen
Carbon Black	1333-86-4	15-30	3.5mg/M3	3.5mg/M3	IARC
Organic Pigments	See Table 2	15-30	3.5mg/M3	3.5mg/M3	No
Synthetic Resins	Various	20-40	N/A	N/A	No
Vegetable Oils	8001 Various	23-35	N/A	N/A	No
Severe Hydrotreated Petroleum Middle Distillate	64742-46-7	10-15	5mg/M3	N/A	No
Cobalt Tallate	61789-52-4	0-1	0.1mg/M3	N/A	IARC

#### 3. HAZARDS IDENTIFICATION

OSHA Hazard Communication 29 CFR 1910.1200.......Carbon Black, Manganese Compound

#### 4. FIRST AID MEASURES

**EFFECTS OF OVEREXPOSURE** 

Skin Contact .......Prolonged contact or repeated exposure may cause minor irritation.

Inhalation .......Excess inhalation of mist or vapor may cause dizziness, nausea or irritation

of nasal and respiratory passages. **Ingestion**.....May cause gastrointestinal irritation.

Medical Conditions aggravated by normal exposure: Persons with dermatitis should avoid skin contact.

Target Organs: ......Skin, eyes, lungs.

Primary Routes of entry

Eyes, inhalation, dermal.

EMERGENCY FIRST AID PROCEDURES

• Eye Contact

Flush with large amounts of water until irritation subsides.

If irritation persists, contact a physician.

• Skin Contact:

Wash with soap and water. Remove contaminated clothing and wash

thoroughly before reusing.

# **5. FIRE FIGHTING MEASURES**

**Explosion Limits**.....LEL: N/A UEL: N/A

Extinguishing Media......Foam, carbon dioxide, dry chemical. Water spray may be

applied to cool exposed closed containers.

Monoxide and Carbon Dioxide generated as combustion products.

Special Fire Fighting Procedures......Self-contained breathing apparatus recommended.

## 6. ACCIDENTAL RELEASE MEASURES

Procedure when material spilled or released: Wipe up. Dispose of wipes in approved waste containers.

If petroleum hydrocarbon is used, provide sufficient ventilation.

Waste Disposal Method: Dispose of in accordance with Federal, State and Local regulations.

#### 7. HANDLING AND STORAGE

Avoid storage above 90° F. Keep containers closed when not in use. Handling:

Other Precautions: None required.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Eye Protection: Goggles recommended. Use sufficient ventilation.

Other Protection: None required. Protective Gloves: Gloves recommended.

Respiratory Protection: None required.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Volatile Organic Compounds: (VOCs) 1.34 lbs./gallon 160 Grams/liter Method 24

Boiling Range °F:> 500° Freezing Point °F: N/A Vapor Density vs. Air: Heavier Vapor Pressure: less than 0.04psi

Density: 8.67 lbs./ gallon ASTM D1475 Specific Gravity: 1.00-1.03 Type of Odor: Oily Odor Threshold: N/A

**Appearance:** Black viscous paste. pH: N/A

Evaporation Rate vs. Butyl Acetate: Slower Coefficient of Water/oil Distribution: N/A

Percentage Volatile By Weight: 15.5% ASTM D2369

#### 10. STABILITY AND REACTIVITY

**Product Stability:** Stable

Conditions to Avoid: Strong oxidizing agents. Avoid storage above 90°F.

Keep containers closed when not in use.

Hazardous Decomposition Products: None. **Hazardous Polymerization:** Will not occur.

#### 11. TOXICOLOGICAL INFORMATION

National Toxicology Program (NTP). The International Agency for Research on

Cancer (IARC) lists cobalt compounds as possible human carcinogens (Class 2B.) Mutagen

Teratogen ......No Reproductive Toxicity ......No

# 12. ECOLOGICAL INFORMATION

This product has not been evaluated, but there is no evidence to suggest it will cause any significant environmental problem.

#### 13. DISPOSAL CONSIDERATIONS

Material Released or spilled: This product is not regulated under the Federal Resource Conservation and Recovery Act (RCRA) as a hazardous waste. State and/or local regulations may apply. Spill should be contained, absorbed with suitable absorbent material and placed in suitable containers for disposal in a licensed facility in accordance with Local, State and Federal laws. Do not discharge into waterways or sewer systems.

#### 14. TRANSPORT INFORMATION-**DOT (HM 181)**: Not required – **Shipping Labels**: None required

#### 15. REGULATORY INFORMATION

direct or indirect contact with food.

EINECS (European Economic Community).......All ingredients listed.

California Proposition 65......None

CONEG Legislation.......Meets all current State and Heavy Metal limitations.

Canadian WHMIS......Controlled product

Vegetable Ink Printing Act of 1994 ......Meets the 20% minimum requirement of vegetable oil in sheet fed inks.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best of the knowledge of Van Son Holland Ink Corporation of America. The data on this sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The hazards covered are believed to be those most likely to occur in the reasonable or ordinary use of these materials. Van Son Holland Ink Corporation of America assumes no legal responsibility for use or reliance on this data.