



**Material Safety Data Sheet –  
Van Son Anti Skin Mechanical Pump Spray**  
Date 2/6/2001

<b>H</b>		<b>M</b>		<b>I</b>	<b>S</b>
<b>Hazard Ratings</b>					
Minimal	0	Serious	3	<b>Health</b>	<b>1</b>
Slight	1	Severe	4	<b>Flammability</b>	<b>2</b>
Moderate	2			<b>Reactivity</b>	<b>0</b>

Material Safety and Data Sheet prepared by Gus Lindquist, Consultant

**1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

**DISTRIBUTOR:** Van Son Holland Ink Corporation of America  
92 Union Street, Mineola, NY 11501

**Emergency Telephone:** 516-294-8811

**Product Class:** Pump Spray Non Aerosol

**Trade Name:** Van Son Anti Skin Mechanical Pump Spray

**MANUFACTURER:**

Chemical Products Company

10 Beach Street, North Warren, PA 16365

**Chemtrec 24 Hour Emergency No-**800-424-9300

**Manufacturer's Code ID:** VS 2001

**2. INGREDIENT COMPOSITION INFORMATION**

Ingredient	CAS No.	WT%	OSHA (PEL)	ACGIH (TLV)	Carcinogen
Petroleum Naptha	64742-48-9	8-15	300ppm	N/A	No
Hydrotreated Stoddard Solvent	8052-41-3	57-73	500ppm	500ppm	No
Light Hydrotreated Petroleum Distillate	64742-47-8	7-13	100ppm	N/A	No
Antioxidant	128-37-0	2-7	N/A	N/A	No
Vegetable Oil	67746-08-1	3-9	N/A	N/A	No

**3. HAZARDS IDENTIFICATION**

OSHA Hazard Communication 29 CFR 1910.1200.....Hydrotreated Stoddard Solvent

**4. FIRST AID MEASURES**

**EFFECTS OF OVEREXPOSURE**

- Eye Contact**– Direct contact may cause severe irritation.
- Skin Contact**– Prolonged contact or repeated exposure may cause blistering.
- Inhalation**– Excess inhalation of mist or vapor may cause dizziness, nausea or irritation of nasal and respiratory passages.
- Ingestion**– May cause gastrointestinal irritation and diarrhea.
- Medical Conditions aggravated by normal exposure**–Persons with lung congestion should avoid contact. May cause injury to nervous system.
- Target Organs**–Skin, eyes, lungs.
- Primary Routes of entry**–Eyes, inhalation, dermal.

**–CAN CAUSE INJURY TO NERVOUS SYSTEM IF TLV EXCEEDED IN 8 HOUR DAY–**

**EMERGENCY FIRST AID PROCEDURES**

- **Eye Contact**– Gently flush with large amounts of water until irritation subsides. If irritation persists, contact a physician.
- **Skin Contact**– Remove contaminated clothing and wash thoroughly before reusing. Wash affected skin areas with soap and water. Seek medical attention if irritation persists.
- **Ingestion**– If swallowed, do not induce vomiting. Call a physician.
- **Inhalation**– Remove individual to fresh air.

**5. FIRE FIGHTING MEASURES**

- Flash Point**.....Above 132°F Method used: closed cup
- Explosion Limits**.....LEL:1.1/ UEL:9.6
- Extinguishing Media**.....Foam, carbon dioxide, dry chemical. Water spray may be applied to cool exposed closed containers.
- Unusual Fire and Explosion Hazards**.....Dense smoke may be generated when burning. Thermal decomposition causes toxic fumes. Do not store near fire or flame.
- Special Fire Fighting Procedures**.....Self-contained breathing apparatus recommended. Cool with water spray.

**6. ACCIDENTAL RELEASE MEASURES**

- Procedure when material spilled or released:** Wipe up. Dispose of wipes in approved waste containers. Vapors may ignite. Material partly water soluble. May float and spread.
- Waste Disposal Method:** Dispose of in accordance with Federal, State and Local regulations.

**7. HANDLING AND STORAGE**

**Handling:** Avoid storage above 90°F. Keep from flame or sparks.  
 Keep containers closed when not in use. Excess heat can cause container bursting.  
**Other Precautions:** Keep out of direct sunlight.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Ventilation**–Use sufficient ventilation.  
**Protective Gloves**–Impermeable gloves recommended to prevent skin irritation and absorption.  
**Respiratory Protection**–NIOSH/MSHA Respirator for heavy usage.  
**Eye Protection**–Goggles and face shield recommended.  
**Other Protection**–Rubber apron recommended.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Volatile Organic Compounds: (VOCs)</b> 0.85 lbs./gallon	<b>102 Grams/liter Method 24</b>
<b>Boiling Range °F:</b> > 370	<b>Freezing Point °F:</b> N/A
<b>Vapor Density vs. Air:</b> Heavier	<b>Vapor Pressure:</b> 0.29 mm Hg
<b>Density:</b> 6.54 lbs./ gallon ASTM D1475	<b>Specific Gravity:</b> 0.785
<b>Type of Odor:</b> Ethereal	<b>Odor Threshold:</b> Low
<b>Appearance:</b> Clear liquid	<b>pH:</b> N/A
<b>Evaporation Rate vs. Butyl Acetate:</b> N/A	<b>Coefficient of Water/oil Distribution:</b> N/A
<b>Percentage Volatile By Weight:</b> 90% ASTM D2369	

**10. STABILITY AND REACTIVITY**

**Product Stability:** Stable  
**Conditions to Avoid:** Strong oxidizing agents, acids and bases. Avoid storage above 90°F.  
 Keep containers closed when not in use.  
**Hazardous Decomposition Products:** Carbon Monoxide, Carbon Dioxide and smoke.  
**Hazardous Polymerization:** Will not occur.

**11. TOXICOLOGICAL INFORMATION**

**Carcinogen** .....Contains no materials that are considered carcinogenic by National Toxicology Program (NTP), International Agency for Research on Cancer (IARC) or OSHA.  
**Mutagen** .....No  
**Teratogen** .....No  
**Reproductive Toxicity** .....No

**12. ECOLOGICAL INFORMATION**

This product has not been evaluated, but there is no evidence to suggest it will cause any significant environmental problem.

**13. DISPOSAL CONSIDERATIONS**

**Material Released or spilled:** This product is not regulated under the Federal Resource Conservation and Recovery Act (RCRA) as a hazardous waste. State and/or local regulations may apply. Spill should be contained, absorbed with suitable absorbent material and placed in suitable containers for disposal in a licensed facility in accordance with Local, State and Federal laws. Do not discharge into waterways or sewer systems.

**14. TRANSPORT INFORMATION–DOT (HM 181) :** Combustible Liquid N.O.S. NA1993 OSHA Flammable Liquid  
**Shipping Labels:** Combustible Liquid N.O.S. NA1993 (Petroleum Naptha and Isaparaffinic Hydrocarbon) Label. Packaging Group III.

**15. REGULATORY INFORMATION**

**TSCA (Toxic Substance Control Act)**.....All ingredients listed in TSCA Inventory  
**CERCLA Superfund 40CFR 117.302**.....Contains no reportable materials  
**SARA Title III**.....None  
**FDA**..... This product is not a food additive and would not have approval for direct or indirect contact with food.  
**EINECS (European Economic Community)**.....All ingredients listed.  
**California Proposition 65**.....None  
**CONEG Legislation**.....Meets all current State and Heavy Metal limitations.  
**Canadian WHMIS**.....Controlled product.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best of the knowledge of Van Son Holland Ink Corporation of America. The data on this sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The hazards covered are believed to be those most likely to occur in the reasonable or ordinary use of these materials. Van Son Holland Ink Corporation of America assumes no legal responsibility for use or reliance on this data.