

**Material Safety Data Sheet –
Rapid One Step Glaze Remover**
Date: 2/6/2001



		H	M	I	S		
		Hazard Ratings				Health	1
Minimal	0	Serious	3				
Slight	1	Severe	4	Flammability	2		
Moderate	2			Reactivity	0		

Material Safety and Data Sheet prepared by Gus Lindquist, Consultant

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

DISTRIBUTOR: Van Son Holland Ink Corporation of America
92 Union Street, Mineola, NY 11501

Emergency Telephone: 516-294-8811

Product Class: Blanket Cleaner and Conditioner

Trade Name: Rapid One Step Glaze Remover

MANUFACTURER:

Chemical Products Company

10 Beach Street, North Warren, PA 16365

Chemtrec 24 Hour Emergency No-800-424-9300

Manufacturer's Code ID: VS 2018, 2028, 2029

2. INGREDIENT COMPOSITION INFORMATION

Ingredient	CAS No.	WT%	OSHA (PEL)	ACGIH (TLV)	Carcinogen
Dipropylene Glycol	34590-94-8	–	100ppm	100ppm	No
Propylene Glycol	107-98-2	–	N/A	100ppm	No
Petroleum Hydrocarbon	64792-95-6	–	100ppm	100ppm	No
Triton X100	902-93-1	–	N/A	N/A	No
Monoethanolamine	141-43-5	–	N/A	N/A	No
Weight percentage is Trade Secret in Massachusetts, New Jersey and Pennsylvania					

3. HAZARDS IDENTIFICATION

OSHA Hazard Communication 29 CFR 1910.1200.....None

4. FIRST AID MEASURES

EFFECTS OF OVEREXPOSURE

Eye Contact– Direct contact may cause severe irritation and burning.

Skin Contact– Prolonged contact or repeated exposure may cause irritation and defatting.

Inhalation– Excess inhalation of mist or vapor may cause dizziness, nausea or irritation of nasal and respiratory passages.

Ingestion– May cause gastrointestinal irritation and diarrhea.

Medical Conditions aggravated by normal exposure–Persons with dermatitis should avoid skin contact.

Target Organs– Skin, eyes, nervous system.

Primary Routes of entry–Eyes, inhalation, dermal.

**–DO NOT EXCEED TLV FOR 8 HOUR DAY. LONG EXPOSURE CAN INJURE NERVOUS SYSTEM–
EMERGENCY FIRST AID PROCEDURES**

- **Eye Contact–** Gently flush with large amounts of water until irritation subsides. If irritation persists, contact a physician.
- **Skin Contact–** Remove contaminated clothing and wash thoroughly before reusing. Wash affected skin areas with soap and water. Seek medical attention if irritation persists.
- **Ingestion–** If swallowed, do not induce vomiting. Call a physician or poison control center.
- **Inhalation–** Remove individual to fresh air.

5. FIRE FIGHTING MEASURES

Flash Point.....Above 116°F Method used: closed cup

Explosion Limits.....LEL:N/A– UEL:N/A

Extinguishing Media.....Foam, carbon dioxide, dry chemical. Water spray may be applied to cool exposed closed containers.

Unusual Fire and Explosion Hazards.....Dense smoke may be generated when burning. Carbon monoxide and carbon dioxide generated as combustion products.

Special Fire Fighting Procedures.....Self-contained breathing apparatus recommended.

6. ACCIDENTAL RELEASE MEASURES

Procedure when material spilled or released: Wipe up. Dispose of wipes in approved waste containers for flammable liquids. If petroleum hydrocarbon is used, provide sufficient ventilation.

Waste Disposal Method: Dispose of in accordance with Federal, State and Local regulations.

7. HANDLING AND STORAGE

Handling: Avoid storage above 90°F. Keep from flame or sparks.
Keep containers closed when not in use.

Other Precautions: None required.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation–Use sufficient ventilation.

Protective Gloves–Impermeable gloves recommended to prevent skin irritation and absorption.

Respiratory Protection–If TLV exceeded, use NIOSH Respirators.

Eye Protection–Safety glasses are recommended.

Other Protection–None recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Volatile Organic Compounds: (VOCs) 2.60 lbs./gallon	299 Grams/liter Method 24
Boiling Range °F: > 305-307	Freezing Point °F: N/A
Vapor Density vs. Air: Heavier	Vapor Pressure: .26mm Hg at 25°C
Density: 6.90 lbs./ gallon ASTM D1475	Specific Gravity: less than 1.00
Type of Odor: Sweet aromatic	Odor Threshold: High
Appearance: Rose colored liquid	pH: N/A
Evaporation Rate vs. Butyl Acetate: Slower	Coefficient of Water/oil Distribution: N/A
Percentage Volatile By Weight: 50% ASTM D2369	

10. STABILITY AND REACTIVITY

Product Stability: Stable

Conditions to Avoid: Strong oxidizing agents, acids and bases. Avoid storage above 90°F. Keep containers closed when not in use. Avoid sparks and flames.

Hazardous Decomposition Products: Carbon Monoxide, Carbon Dioxide and smoke.

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Carcinogen Contains no materials that are considered carcinogenic by National Toxicology Program (NTP), International Agency for Research on Cancer (IARC) or OSHA.

Mutagen No

Teratogen No

Reproductive Toxicity No

12. ECOLOGICAL INFORMATION

This product has not been evaluated, but there is no evidence to suggest it will cause any significant environmental problem.

13. DISPOSAL CONSIDERATIONS

Material Released or spilled: This product is not regulated under the Federal Resource Conservation and Recovery Act (RCRA) as a hazardous waste. State and/or local regulations may apply. Spill should be contained, absorbed with suitable absorbent material and placed in suitable containers for disposal in a licensed facility in accordance with Local, State and Federal laws. Do not discharge into waterways or sewer systems.

14. TRANSPORT INFORMATION– DOT (HM 181) : Combustible Liquid N.O.S. NA 1993

Shipping Labels: Combustible Liquid N.O.S. NA 1993 (Petroleum Naptha and Glycol Ethers)

15. REGULATORY INFORMATION

TSCA (Toxic Substance Control Act).....All ingredients listed in TSCA Inventory

CERCLA Superfund 40CFR 117.302.....Contains no reportable materials

SARA Title III.....None

FDA..... This product is not a food additive and would not have approval for direct or indirect contact with food.

EINECS (European Economic Community).....All ingredients listed.

California Proposition 65.....None

CONEG Legislation.....Meets all current State and Heavy Metal limitations.

Canadian WHMIS.....Controlled product.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best of the knowledge of Van Son Holland Ink Corporation of America. The data on this sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The hazards covered are believed to be those most likely to occur in the reasonable or ordinary use of these materials. Van Son Holland Ink Corporation of America assumes no legal responsibility for use or reliance on this data.