Date revised : December 19, 2012

Sheet-fed (RB) Offset Printing Ink

1. Product and company identification

Product class	Offset Printing Ink, Non-Oxidizing	
Product name	RB Color Series	
Manufacturer for		
and Distributed by	Tokyo Printing Ink Corporation U.S.A.	
Address	2695 Temple Avenue	
	Signal Hill, CA 90755	
Telephone	(562) 424-2226	

2. Composition / information on ingredients

Ingredients		CAS Number	Content (w/w)
Synthetic Resins		Various	20-45
Vegetable	Linseed Oil	8001-26-1	0-15
Oils	Soybean Oil	8001-22-7	0-25
Polyethylene	Wax	9002-88-4	0-5
	C.I. Pigment Yellow 12	6358-85-6	0-30
	C.I. Pigment Yellow 13	5102-83-0	0-30
	C.I. Pigment Yellow 83	5567-15-7	0-30
	C.I. Pigment Red 48:1	7585-41-3	0-30
	C.I. Pigment Red 53:1	5160-02-1	0-30
	C.I. Pigment Red 57:1	5281-04-9	0-30
	C.I. Pigment Red 81:4	85959-61-1	0-30
Pigments	C.I. Pigment Red 170	2786-76-7	0-30
	C.I. Pigment Red 188	61847-48-1	0-30
	C.I. Pigment Blue 15:3	147-14-8	0-30
	C.I. Pigment Blue 61	1324-76-1	0-30
	C.I. Pigment Green 7	1328-53-6	0-30
	C.I. Pigment Violet 3	1325-82-2	0-30
	C.I. Pigment Black 7	1333-86-4	0-30
	C.I. Pigment White 18	471-34-1	0-30

Generally Classified as Non Toxic

3. Hazards identification

None if used properly.

4. First-aid measures

labalation	Move to fresh air condition. Aid in breathing and get medical	
Inhalation	attention, if necessary.	
Skin	Remove contaminated clothing and wash well with soap	
SKIII	and water.	
Eye	Flush with plenty of water immediately for at least 15 minutes	
Суе	and get medical attention.	
Ingostion	Drink a large quantity of water. If available, milk is better. Get	
Ingestion	medical attention.	

5. Fire-fighting measures

Flash point	150-160°C (Open air)				
Explosion limits	Upper: N/A Lower: N/A		/A		
Extinguish media	Fog, Carbon Dioxide, Foam, Dry Chemical		cal		
Special fire fighting procedures	Self	contained	breathing	apparat	Js is
special fire fighting procedures	reco	mmended.			
Unusual fire and explosion hazards	s N/A				

6. Accidental release measures

Wipe out and placed in a suitable covered container for disposal. Dispose in accordance with local, country, state and federal regulation.

7. Handling and storage

Precaution in handling and storing	Store in sealed container and keep away from		
	high temperature (under than 40°C), direct		
	sunlight and excessive moisture.		
Average shelf life	More than 6 months		

8. Exposure controls / personal protection

Respiration	Use respirator, if necessary.	
Ventilation	Use general and local exhaust ventilation.	
Skin	Rubber gloves are recommended.	
Eye	Safety glasses are recommended.	
Other	Use apron, coverall and boots, if necessary.	

9. Physical and chemical properties

Appearance	Viscous paste
Color	Various
Odor	Oily odor
Molecular weight	N/A
рН	N/A

Specific gravity	0.80-1.05 (25°C)	
Boiling point	N/A	
Vapor density	N/A	
Vapor pressure	N/A	
Solubility in water	Insoluble	
VOC's	< 0.5 lbs/gal	
VOCS	< 5 wt%	

10. Stability and reactivity

Stability	Stable	
Condition to avoid	Heat, Spark, Open flame	
Incompatibility	May react with strong oxidizing agents.	
Hazardous decomposition products May evolve noxious fumes carbon oxide, nitrous oxide involved in a fire burning.		
Hazardous polymerization	Not expected.	

11. Toxicological information

Carcinogen	None
Mutagen	None

Teratogen	None
Reproductive toxicity	None

12. Ecological information

There is no evidence to cause environmental problem.

13. Disposal considerations

Dispose in accordance with local, country, state and federal regulation. Do not discharge into sewer systems.

14. Transport information

There is no hazardous information.

15. Regulatory information

TSCA	All ingredients are listed.	
(Toxic Substance Control Act)		
CERCLA / Superfund, 40 CFR 117.302		
(Comprehensive Environment Response,	Contains no reportable components.	
Compensation, and Liability Act)		
SARA Title III		
(Superfund Amendments and	Cobalt compound is used as drier.	
Reauthorization Act)		
FDA	These inks would not be approved to	
(Food and Drug Administration)	contact directly with food.	
EINECS	All materials are listed.	
(European Economic Community)		
California Proposition 65	Carbon black is included as pigment.	
CONEG Legislation	Meets all current state and heavy metal	
(Coalition of Northeastern Governors)	limitations.	

16. Other information

This information is based on our current level of knowledge. It is intended describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.